

Cetis Teledex E103IP RediDock IP Phone



Product Name: Cetis Teledex E103IP RediDock IP Phone

Manufacturer: -

Model Number: E103IP-RD

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Cetis Teledex E103IP RediDock IP Phone

The Cetis Teledex E103IP is a RediDock IP phone with 1 SIP line. The Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, the E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller.

Cetis Teledex E103IP Key Features

- Available Frequencies: 18 GHz and 19 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- PoE Enabled
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black *Two-line only

Cetis Teledex E103IP - Technical Specifications

General

- Standard Color: Ash and Black
- Footprint (Desk): 45° (1143cm) (w) x 8° (2032cm) (l) x 363° (922cm) (d) (max height with desk stand)
- Footprint (Wall): 45° (1143cm) (w) x 8° (2032cm) (l) x 15° (381cm) (d) (depth from wall mount)
- Footprint (ETrim/RediDock): Same as above
- Weight: 20 lbs (09kg)
- Weight (ETrim/Redidock): 12 oz (034kg)
- Frequency: 19 GHz or 18 GHz
- Power: Power over Ethernet (POE) 8023af Compliant
- Power (Cordless): Remote Charging Station includes Handset with Battery & A/C adaptor
- Standby Time (Cordless): 10 days
- Talk Time (Cordless): 6 hours
- Range (Cordless): 100ft (30m)
- Humidity: 65% ± 20%
- Temperature: 77°&F ± 50°° (25°°C ± 10°°C)
- Packaging: 10 per carton
- Packaging (RediDock): 20 per carton
- Faceplate Size: Full length

Cetis Teledex E103IP RediDock IP Phone

• FCC Specifications: FCC Part 15 Subpart B: 2009
• Safety Standard: UL - 60950-1 2nd edition ADA/HAC
• Handset: 10 ft (3048m)
• Line Cord: RJ14 line cord - 15 ft (45m)
• Line Cord (Cordless): RJ45 line cord - 15 ft (45m)
• RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

Please Enquire

Options available for Cetis Teledex E103IP RediDock IP Phone :

Colour

Ash (EV021318S00H), Black (EV011318S00H).