

## Cetis Teledex E203IP 7GSK IP Phone



Product Name: Cetis Teledex E203IP 7GSK IP Phone

Manufacturer: -

Model Number: E203IP-7GSK

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Cetis Teledex E203IP 7GSK IP Phone

The Cetis Teledex E203IP is an IP phone with 2 SIP lines. The Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, the E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller.

### Cetis Teledex E203IP Key Features

- Available Frequencies: 18 GHz and 19 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- PoE Enabled
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference\*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black \*Two-line only

### Cetis Teledex E203IP - Technical Specifications

#### General

- Standard Color: Ash and Black
- Footprint (Desk): 4.5" (1143cm) (w) x 8" (2032cm) (l) x 3.63" (922cm) (d) (max height with desk stand)
- Footprint (Wall): 4.5" (1143cm) (w) x 8" (2032cm) (l) x 1.5" (381cm) (d) (depth from wall mount)
- Footprint (ETrim/RediDock): Same as above
- Weight: 20 lbs (09kg)
- Weight (ETrim/Redidock): 12 oz (034kg)
- Frequency: 19 GHz or 18 GHz
- Power: Power over Ethernet (POE) 8023af Compliant
- Power (Cordless): Remote Charging Station includes Handset with Battery & A/C adaptor
- Standby Time (Cordless): 10 days
- Talk Time (Cordless): 6 hours
- Range (Cordless): 100ft (30m)
- Humidity: 65% &plusmn; 20%
- Temperature: 77deg;F &plusmn; 50deg; (25deg;C &plusmn; 10deg;C)
- Packaging: 10 per carton
- Packaging (RediDock): 20 per carton
- Faceplate Size: Full length

## Cetis Teledex E203IP 7GSK IP Phone

• FCC Specifications: FCC Part 15 Subpart B: 2009  
• Safety Standard: UL - 60950-1 2nd edition ADA/HAC  
• Handset: 10 ft (3048m)  
• Line Cord: RJ14 line cord - 15 ft (45m)  
• Line Cord (Cordless): RJ45 line cord - 15 ft (45m)  
• RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

**Please Enquire**

---

Options available for Cetis Teledex E203IP 7GSK IP Phone :

**Colour**

[Black \(EV012318S07D\)](#), [Ash \(EV022318S07D\)](#).