

## Cetis Teledex M103IP5 1 Line SIP Phone



Product Name: Cetis Teledex M103IP5 1 Line SIP Phone

Manufacturer: -

Model Number: M103IP5

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Cetis Teledex M103IP5 1 Line SIP Phone

The Cetis Teledex M103IP5 is an IP phone with a SIP speaker, 1 line, 1.8GHz, 5 Guest Service Keys and 1 USB port.

The M Series Standard hotel phones are cordless and are available with 0, 5, or 10 guest service keys or 0, 3, or 6 on the RediDock remote handset kit. The USB charging ports on the phone and RediDock support smart device recharging. OneTouch voice mail retrieval automates guest messaging. AutoSync registers RediDock handsets with the base to eliminate connection failures and misplaced handsets.

#### M Series Standard VoIP Cordless Key Features

• Available Frequencies: 1.8 GHz and 1.9 GHz

• Single or Two-line speakerphones

• Handset speakerphone

• PoE Enabled

• Supports up to five handsets, including one on the base and four remotes (RediDocks)

• 0, 5, or 10 configurable guest service keys on base

• 0, 3, or 6 configurable guest service keys on handset

• Patented OneTouch voice mail retrieval

• Dual Neon/LED message-waiting light

• 1 side USB power port for device charging

• HAC/VCH (ADA) compliant handset volume boost

• Electronic 3-way conference (2-line only)

• Full-length customizable paper faceplate

• Available in Black

#### Teledex M - Technical Specifications

##### General

• Standard Color: Black

• Footprint: 217 mm x 147.2 mm x 93 mm

• Footprint (Trimline): 240 mm x 76.2 mm x 64 mm

• Footprint (RediDock): 215 mm x 66 mm x 69 mm

• Weight: 1100 g

• Weight (Trimline): 600 g

• Weight (RediDock): 650 g

• Frequency: 1.9 GHz or 1.8 GHz

• Power: Power over Ethernet (POE) 802.3af Compliant

• Power (Cordless): Remote Charging Station includes Handset with Battery & A/C adaptor

• Standby Time (Cordless): 10 days

• Talk Time (Cordless): 6 hours

• Range (Cordless): 100ft (30m)

• Humidity: 65% &plusmn; 20%

• Temperature: 77&deg;F &plusmn; 50&deg; (25&deg;C &plusmn; 10&deg;C)

• Packaging: 10 per carton

• Packaging (RediDock): 20 per carton

## Cetis Teledex M103IP5 1 Line SIP Phone

• Faceplate Size: . Full length  
• FCC Specifications: FCC Part 15 Subpart B: 2009  
• Safety Standard: UL - 60950&ndash;1 2nd edition ADA/HAC  
• Handset Coil Cord: 10 ft (3.048m)  
• Line Cord: . RJ14 line cord - 15 ft (4.5m)  
• Line Cord (Cordless): RJ45 line cord - 15 ft (4.5m)  
• RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

**Please Enquire**

---