

## CyberData SIP Loudspeaker Amplifier AC Powered (011404)



Product Name: CyberData SIP Loudspeaker Amplifier AC Powered (011404)

Manufacturer: -

Model Number: -

Please Note: This product has been discontinued. For an alternative, please see the CyberData SIP Loudspeaker Amplifier - PoE (011405).

CyberData SIP Loudspeaker Amplifier AC Powered (011404)

The CyberData SIP-enabled Loudspeaker Amplifier (011404) provides an easy method for implementing a loud IP-based overhead paging system for loud areas, warehouses, manufacturing areas, and outdoor areas.

CyberData 011404 Key Features

- SIP Enhanced interoperability for hosted environments CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData
- Security Features: Support for security code access for SIP paging Autoprovisioning via HTTPS web based configuration
- Support for G.722 codecs
- 802.11q VLAN tagging
- Configurable sense input for use with fault detection
- Configurable event generation for device health and status monitoring
- Optional direct connect RGB strobe kit connection
- 9 user-uploadable page messages

With up to 9 user-stored messages, the Amplifier provides direct drive of up to two 8 Ohm horns. The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the Loudspeaker Amplifier can be configured to listen to multicast address and port number combinations to form paging zones.

CyberData 011404 - Technical Specifications  
Features

- Packaged in a NEMA 3R/IP42-rated enclosure SIP and Simultaneous Multicast
- Dual-speed ethernet 10/100 Mbps
- Web-based configuration
- PoE 802.3at and 802.3af-enabled Line-in for background music
- Line-out connector
- DTMF controlled relay
- Direct 8 Ohm speaker drive
- User-uploadable tones and messages
- Digital and manual volume control
- Second SIP endpoint "Night Ringer"
- Autoprovisioning
- Auto-call voice message from input port sense Can support two horns
- HTTP Command Interface
- 10 channel prioritized Multicast ports
- Built-in diagnostics
- Delayed page support
- Cisco SRST

General

## CyberData SIP Loudspeaker Amplifier AC Powered (011404)

• Ethernet I/F 10/100 Mbps Protocol SIP RFC 3261 Compatible Power Input PoE 802.3at or 802.3af Audio Output 802.3at - SPL 117 dB @ 1 meter (When used with the 011068 Mini Horn.)  
• Line Out: Output Signal Amplitudes 2.0 VPP maximum Output Level +2dBm nominal Total Harmonic Distortion 0.5% maximum Output Impedance 10k ohm  
• Operating Temperature -10 degrees C to 50 degrees C (14 degrees F to 122 degrees F)  
• Payload Types G.711  $\mu$ -law, G.711 a-law, and G.722 + Singlewire HD  
• Dimensions 10 in. [254 mm] Length 4 in. [101.6 mm] Width 14 in. [355.6 mm] Height  
• Boxed Weight 6.5 lbs. [2.95 kg]  
• Warranty 2 Years Limited  
• Part Number 011404  
• Loudspeaker Part Number 011068

**Please Enquire**

---