

## Spectralink 8440 EU Blue Handset SIP only



Product Name: Spectralink 8440 EU Blue Handset SIP only

Manufacturer: -

Model Number: 2200-37165-101

Please Note: This product is end of life. For an alternative, please see the other Spectralink phones.

Spectralink 8440 EU Blue Handset SIP only

The Spectralink 8440 EU Blue Handset SIP only deliver on a fundamental need for enterprise-grade on-site voice mobility. Characterized by market-leading HD voice quality, durability, broad telephony and WLAN interoperability, the Spectralink 84-Series handsets deliver a reliable user experience and predictable return on investment.

Spectralink 8440 EU Blue Key Features

- Four (4) context-sensitive softkey buttons
- Push-to-Talk
- Five-way navigation and select control
- Home & Back navigation keys
- Up/Down volume control
- Barcode reader (8452/8453 handsets)
- Start and End Keys
- Panic/Duress

And with Spectralink VQO built into every 84-Series device, you get an engineered system that delivers superior voice quality. Spectralink VQO links seamlessly to access points using a proprietary, adaptive, algorithm. And only advanced, guided implementation by the Spectralink experts can ensure crystal-clear communication.

It's our Performance Promise. The Spectralink 84-Series enhances the customer value proposition through an optional integrated barcode scanner and an enhanced standards-based applications interface. In partnership with the Spectralink applications development ecosystem, the Spectralink 84-Series products enable new opportunities for end-user productivity solutions.

Spectralink 8440 EU Blue - Technical Specifications  
DISPLAY

- 2.2 in. (55.9 mm)
- 240 x 320 resolution
- 65,000 color palette

STATUS LED

- Message (voicemail) waiting
- Out of coverage
- Phone ringing

PERIPHERAL INTERFACES

- Micro USB interface for wall charging and configuration
- 2.5mm connector for wired headset
- Bluetooth

BATTERIES

## Spectralink 8440 EU Blue Handset SIP only

- Two easy-access cosmetic battery capacity options
- Standard – Up to 8 hrs talk time, 80hrs standby time
- Enhanced – Up to 12 hrs talk time, 120hrs standby time May vary based on scanner, applications usage, screen brightness settings, etc.

### DURABILITY

- Drop/shock: MIL STD 810F, method 516.5 procedure IV
- Ingress protection standard: IP 64 per IEC 60529
- Rubberized molding
- Magnesium LCD mounting

### ENVIRONMENTAL

- Operational temperature: 32 - 104° F (0 - 40° C)
- Storage temperature: -22 -140° F (-30 - 60° C)

### DIMENSIONS & WEIGHT

- Dimensions 5.8 x 2.1 x 1.0 inc. (147 x 53 x 25 mm) 5.7 x 2.1 x 1.3 in. (146 x 54 x 34 mm )
- Weight 5.1 oz (144.6 gr.) 5.7 oz (161.6 gr.) As measured with standard battery

### Wi-Fi

#### • BAND FREQUENCY DATA RATES

- 802.11a 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.725 - 5.825 GHz 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11b 2.4 - 2.4835 GHz 1, 2, 5.5, 11 Mbps
- 802.11g 2.4 - 2.4835 GHz 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11n\* 2.4 & 5 GHz 21.7, 43.3, 65, 72.2 Mbps 2.4GHz and 5GHz dynamic band roaming supported \*Single-stream, 20MHz channel with SGI

### Bluetooth Headset Support

- Version 2.1, HSP Version 1.2
- Class 1 support with range of ~10 meters

### CALL HANDLING FEATURES\*

- Up to six (6) telephone line appearances
- Call Hold/Resume function
- Last Call Return
- Music on Hold
- Consultation Hold
- Call Transfer (Attended, Unattended)
- Overlap dialing
- Bridged Line Appearance (BLA)
- Three-Way Conferencing (local)
- Find-Me call forking
- Call Screening (Incoming, Outgoing)
- Automatic Answer
- Call Park & Retrieve
- Group Call Pickup
- Call Waiting

## Spectralink 8440 EU Blue Handset SIP only

- Multiple Calls per Line
- Do Not Disturb
- Calling party ID (Name and Number)
- Called party ID (Name and Number)
- Connected party ID (Name and Number)
- Call Forward (Busy, No Answer, Unconditional)
- Call Reject \*Summary only &ndash; actual feature support will vary among call platforms

### CODECS

- G.711 (a-law, u-law), G.729, G.722, G.722.1

### PUSH-TO-TALK (PTT)/PAGING

- On-board native &lsquo;walkie-talkie&rsquo; capability
- One-to-one, one-to-many broadcast communication
- 24 configurable channels
- Priority, default channel

### ADDITIONAL TELEPHONY FEATURES

- RTCP (RFC 3550, RFC 1889)
- Call server redundancy
- Predictive dialing from contacts list
- Recent call lists

### USER PROFILES

- Downloadable to any handset with ID and Login

### PERSONAL SAFETY

- Duress/Panic button
- No motion, running, tilt detection
- Alarm notifications

### ADDITIONAL

- Intuitive Graphical User Interface
- Selectable wallpaper/background
- Adjustable display brightness
- Backlit keypad with adjustable timeout period
- Ten (10) selectable ring tones
- Ten (10) selectable alert tones
- Multiple vibrate cadence options
- Vibrate-to-ring options
- Audible and vibrate notification options
- Speed dial menu list
- Contacts directory with support for 1000 local entries
- Call logs - Minimum of 20 logged entries for each call type (Incoming, dialed, and missed)
- Emergency system-wide speed dial
- Auto-answer & any key answer capability
- Selectable ring tones
- Unicode UTF-8 Multilingual User Interface

## Spectralink 8440 EU Blue Handset SIP only

### PROVISIONING

- Server based central provisioning via FTP, FTPS, TFTP, HTTP or HTTPS
- Centralized user administration
- Provisioning and call server redundancy
- Initial configuration via USB
- Unicode UTF-8 Multilingual User Interface

### PERFORMANCE AND FAULT MANAGEMENT

- On-board site survey and diagnostics tools
- Enhanced syslog reporting
- Roaming and handoff reporting
- Event logging
- Hardware diagnostics
- Status and status reporting
- PING support (initiate and response)
- Traceroute

### CONFIGURATION MANAGEMENT

- User and administrator login and privileges
- PC-connected (USB) and remote over-the-air configuration management

### XML APPLICATIONS PROGRAM INTERFACE

- Standards-based XHTML API
- On-board WebKit-based browser (JavaScript, CSS, DOM) for rich applications integration
- Corporate directory access LDAP

### SPECTRALINK OPEN APPLICATION INTERFACE (OAI)

- Backward compatibility with Spectralink OAI applications

### INSTANT MESSAGING

- Handset-to-handset, PC client-to-handset IM support via Microsoft® OCS and/or Microsoft Lync

### REAL TIME LOCATION SERVICES (RTLTS)

- Embedded RTLTS beacon (Ekahau) for location tracking
- AeroScout

### CALENDAR - EXCHANGE SERVER INTEGRATION

- Day and month view
- Meeting reminders

### AUDIO QUALITY

- TIA 810B, TIA 920 audio quality standards
- Full-duplex audio (compliant with IEEE 1329 full duplex standards)
- Voice activity detection (VAD)
- Comfort noise fill

## Spectralink 8440 EU Blue Handset SIP only

- Adaptive jitter buffer & packet loss concealment
- Acoustic echo cancellation & background noise suppression

### QUALITY OF SERVICE (QOS)

- Wi-Fi Multimedia (WMM)
- WMM-Power Save
- WMM-Admission Control (draft)
- IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

### SECURITY

- WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-FAST, PEAP-MSCHAPv2) with Opportunistic Key Caching (OKC) and Cisco Client Key Management (CCKM)
- Media encryption via Secure Real-Time Protocol (SRTP)
- SIP signaling encryption via Transport Layer Security (TLS)
- Server-based configuration file encryption (AES 128 bit)
- HTTPS secure provisioning
- Support for signed software executables

### Strong support for networking standards

- Address assignment via Manual or Dynamic host configuration protocol (DHCP)
- Domain name resolution via Domain Name Service (DNS)
- Time and date synchronization using Simple Network Time Protocol (SNTP)
- Lightweight Directory Access Protocol (LDAP) for directory lookup and download
- IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

### High-performance scanning

- Type 1D/2D Area Imagers
- Light Source 617 nm Highly Visible LED (5)
- Scan Angle 38.9°; Horiz., 25.4°; Vert.
- Label print contrast Down to 25%
- Resolution Optical Resolution 752 x 480 pixels
- Reading distance Up to 34 in. (864 mm)

### BARCODE SYMBOLOGIES

- 1D: RSS, Stacked RSS, RSS-14, GS1-DataBar, Code 39, Code 93, Code 128, UPC (E&A)
- 2D: Aztec, Codabar, Code 11, Code 39, Code 93/93i, Code 128, GS1-128, ISBT8, Databar (RSS), Datamatrix, EAN13, EAN8, Interleaved 2 of 5, Micro PDF 417, MSI, PDF 417, Plessey, QC code, Telepen, UPCA, UPCE, UPC/EAN

**Please Enquire**