

Rhino Ceros 1U Chassis, 80GB HDD (CerosMini-80GB-ST) W/ RAID1



Product Name: Rhino Ceros 1U Chassis, 80GB HDD (CerosMini-80GB-ST) W/ RAID1

Manufacturer: -

Model Number: CEROSMINI-80G-RAIDST

Availability: Discontinued Please note the Rhino Ceros 80GB HDD has been discontinued. For alternatives please see the Rhino Ceros 1U Standalone range. Providing reliable, flexible, and leading-edge solutions for a demanding industry. Managing your open source telecommunication needs has never been easier than with Rhino products. Ceros provides instant credibility to your Value Added Reseller (VAR) product line, by providing an unmarked PC chassis that is simply customized by editing a simple four line by 40 character text file. The text in the file is displayed on the LCD at all times for your customers to visually identify your own branded PBX product. Knowing that Rhino products are ready to perform right out of the box means that you can spend more time developing important customer relationships. The Ceros 1U comes preloaded with Linux and Asterisk, along with all the necessary configurations for the specific installed Rhino hardware. All that is needed is to customize extensions and other outside system environment configurations. The Ceros 1U chassis was designed with VARs in mind. The chassis comes with no external markings or silkscreening, and comes shipped in two cartons -- an outside carton that can be discarded so that a pristine, inside carton can be cleanly shipped to your end customer. Rhino Equipment Corp. offers you a complete line of low cost PCI plug-in cards including Single T1/E1, Dual T1/E1, Quad T1/E1, Quad FXO analog, Octal FXS/FXO and 24-port analog mixed mode analog interfaces. And don't forget the full line of Rhino Channel Bank products, for large scale analog FXS or FXO applications. Rhino designed products are tough. In the rare case of trouble, our technical support staff is ready to give you the support you need, when you need it. Our 5-year, limited warranty means that you can be confident that Rhino will always work hard in your Open Source Telephony application. Features:

- 1/2 5-button keypad
- 1/2 Reset and Power Off functions by pressing two buttons
- 1/2 BMP file insertion allows for your Logo
- 1/2 6 lines for your company information
- 1/2 Menu system allows for viewing important system information
- 1/2 Fully graphical - layout graphic and text on the same display

Standard Ceros 1U Features

- 1/2 Asterisk soft PBX tested
- 1/2 Preloaded with your Asterisk distribution of choice
- 1/2 Accepts all Rhino PCI cards. Full length cards have special anchor brackets to fully secure cards in the chassis
- 1/2 Fully tested and integrated with all install Rhino hardware
- 1/2 1U tall, 17.25" wide x 15" deep external dimensions
- 1/2 Rubber bumper feet
- 1/2 19" mounting brackets - wall or rack, all included in box
- 1/2 Six line Rhino serial OSLI and 5-button navigation keypad
- 1/2 No external monitor or keyboard required
- 1/2 5-year limited warranty
- 1/2 Comes with a Rhino Logoed 1GB USB stick for easy restoration of the disk image

Base Configuration

- 1/2 Intel Atom 1.6GHz CPU with 945 Chipset
- 1/2 80GB 2.5" single hard drive (RAID1 also available)

Rhino Ceros 1U Chassis, 80GB HDD (CerosMini-80GB-ST) W/ RAID1

- 1GB 667MHz DDR memory
- 180W power supply
- Two PCI slots (A Rhino ONLY!)
- Rhino SLI 6-line OSLI and 5-button keypad
- Video, mouse and keyboard ports
- Four USB ports
- One GbE (LAN) (2nd port available via PCI card slot)

Chassis Mechanical Data Size : 1U (1.75") tall 17.25" wide, 15" deep Form
Factor: Rack mount, wall mount, table top Weight : 15 pounds for base configuration

Please Enquire
