

Sangoma SBC with 1 x E1/T1, 25 calls



Product Name: Sangoma SBC with 1 x E1/T1, 25 calls

Manufacturer: Sangoma

Model Number: SBCM-ENT-D0100-025

Sangoma SBC with 1 x E1/T1, 25 calls

The Sangoma SBC with 1 x E1/T1, 25 calls provides full-featured protection and easy interconnection at the edge of enterprise networks.

Features of Sangoma SBC Appliance with 25 Calls

- Browser-based GUI for Easy Configuration
- Traffic Visualization Tools
- Session-based Licensing (No Hidden Fees)
- Enterprise Inter-Site Networking and SIP Trunking Border Control
- Local Security Management for SMBs and Small Enterprises
- Hardware-based Transcoding and Media Handling

What is Session Border Control

IP communications across multiple, sometimes untrusted, networks needs to be normalized, managed and secured. There is a need to guarantee interoperability of multiple devices, carriers and protocols in a transparent way to the user of the network. Session border controllers take care of the conversion between protocols, transcoding, threat prevention, resource limiting, and accounting at the edge of VoIP networks of enterprises and carriers alike.

Applications

- SIP Trunking
- Remote Worker
- Hosted PBX
- Lync SBC
- Core Session Router and Load Balancer

Benefits

- Network Security
- Quality of Service/Quality of Experience
- Connectivity
- Protocol Normalization
- Media Services
- Statistics and Billing
- Regulatory Compliance

Technical Specification

Feature/Function Vega Enterprise SBC

- HDD 32GB SSD
- Power 60W
- Rack Mount Yes
- Ethernet 2x GigE
- Hardware-assisted RTP Yes
- Session Capacity 500
- Field Upgradeable (At No Penalty) Yes
- Hardware-ready for Upgrade to Capacity Yes

VoIP

Sangoma SBC with 1 x E1/T1, 25 calls

- SIP Trunking and Remote Working
- SIP Intrusion Prevention
- SIP Registration Scan Attack Detection
- SIP Request Rate Limiting
- SIP Friendly Load Limitation
- SIP Registration Pass-thru
- SIP Header Normalization
- SIP Malformed Packet Protection
- Advanced NAT Traversal Capabilities
- Topology Hiding
- ENUM Routing

Media Capabilities

- Voice, Video, FAX, IM and Presence Support
- Full RTP Transcoding (G.711, G.722, G.729, G.726, G.723.1, iLBC, AMR, G.722.1)
- T.38 Fax Relay

Session and Monitoring

- Multiple Session Routing Options
- RTCP Statistics Reports
- QoS (ToS or DSCP)
- RADIUS CDR and Authentication
- QoS Monitoring and Reporting

Security

- DDoS / DoS Attack Protection
- Call Security with TLS/SRTP
- Media Security with SRTP
- IPsec Encryption
- IP Firewall

Call Control

- Advanced XML Routing Engine
- Dynamic Load Balancing and Call Routing
- Multiple Call Access Control Options
- Least Cost Routing
- Rate Limiting: Call and Registration
- Endpoint Authentication
- Media Bandwidth Policy
- Intelligent Media Anchoring/Release

Management

- Easy to Use Web Interface
- HTTP XML-based CDR
- Real-time Monitoring and Debugging

Price: £2,240.80