

AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points



Product Name: AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points

Manufacturer: -

Model Number: 61V2B10000AC

Please Note: This product is no longer available. To find an alternative, please see our IP Video Conferencing solutions.

AVer SVC-100 Orbit Point to Point VC System, H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 point MCU

As the next generation of AVer SVC-100 video conferencing system, the SVC100 was endowed with a futuristic design. The most standout feature is the stand with a curved design which supports a powerful 18X total zoom lens. Moreover, H.323, SIP, and Skype for Business support provide endless communication possibilities. The dual-camera/dual-presentation elevates AVer's video conferencing system to the next level; providing users with unparalleled video conferencing experience.

AVer SVC-100 Key Features

- eCam PTZ III camera
- 2-megapixel CMOS sensor
- 18X total zoom
- ±110° pan; +25°/-25° tilt
- 72° FOV (H); 43° FOV (V); 82° FOV (diagonal)
- H.323, SIP standards, SIP TLS
- Microsoft Lync 2013, Skype for Business 2015
- Mixed protocols among H.323, SIP, Microsoft Lync 2013, Skype for Business 2015
- Bandwidth 64Kbps ~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

AVer SVC-100 - Technical Specifications

Package contents

- Main system unit (codec)
- eCam PTZ III camera
- SVC microphone array
- IR remote control with batteries
- Power supply
- Cables
- Warranty card
- Quick guide

Communications

- H.323, SIP standards, SIP TLS
- Microsoft Lync 2013, Skype for Business 2015
- Mixed protocols among H.323, SIP, Microsoft Lync 2013, Skype for Business 2015
- Bandwidth 64Kbps ~4Mbps

AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points

- 1/2 RJ45 network LAN (10/100/1000)
- 1/2 Manual bandwidth settings

Camera

- 1/2 eCam PTZ III camera
- 1/2 2-megapixel CMOS sensor
- 1/2 18X total zoom
- 1/2 ±110° pan; +25°/-25° tilt
- 1/2 72° FOV (H); 43° FOV (V); 82° FOV (diagonal)

People video resolutions

- 1/2 HD1080p (1920 x 1080), up to 60fps
- 1/2 HD720p (1280 x 720)
- 1/2 480p (848 x 480)
- 1/2 4CIF (704 x 576)
- 1/2 CIF (352 x 288)
- 1/2 SIF (352 x 240)
- 1/2 All resolutions at 30fps

Content video resolutions

- 1/2 HDMI supported resolutions: - 1080p (1920 x 1080) - 720p (1280 x 720) - D1 (720 x 480) - SXGA (1280 x 1024) - XGA (1024 x 768) - SVGA (800 x 600) - VGA (640 x 480)
- 1/2 DVI (digital) supported resolutions: - 1080p (1920 x 1080) - 720p (1280 x 720) - D1 (720 x 480) - SXGA (1280 x 1024) - XGA (1024 x 768) - SVGA (800 x 600) - VGA (640 x 480)
- 1/2 Output resolutions: - Up to HD1080p (1920 x 1080) up to 60fps

Video standards

- 1/2 H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
- 1/2 H.239 dual video streams
- 1/2 BFCP content sharing
- 1/2 RTMP for live video streaming

Video features

- 1/2 3D denoise

Video inputs

- 1/2 Main camera eCam PTZ III
- 1/2 HDMI for 2nd camera
- 1/2 DVI-I /VGA for presentation
- 1/2 HDMI for presentation

Video outputs

- 1/2 HDMI x 2

AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points

Audio standards

- G.711, G.722, G.722.1, G.728, G.722.1C, AAC-LD

Audio features

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)
- Audio inputs
 - SVC microphone daisy chain up to 4
 - HDMI
 - Line-in (3.5 mm)

Audio inputs

- SVC microphone daisy chain up to 4
- HDMI
- Line-in (3.5 mm)

Audio outputs

- HDMI x 2
- Line-out (3.5 mm)

Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460
- SRTP, H.235

User interface

- Single/dual monitor layout styles
- User-friendly OSD (22 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, PortugueseBrazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish)
- Display/edit site name

Network

- 10/100/1000Mbps
- NAT/firewall traversal (H.460)
- High Efficiency Lost Packet Recovery (HELPeR™)
- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- Network test
- Quality of service (QoS)
- VLAN (802.1Q / 802.1P)
- EAP 802.1x

AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points

Security

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

Web management tool

- Remote management
- Live monitoring
- Firmware update
- Phonebook download/upload/edit
- Restore system settings
- Export call history

Value-added features

- Meeting recording - In meeting and offline recording - Save directly to USB flash drive - Supports screen re-layout during playback - Playback and file conversion via VCPlayer software (.mov and .mp4 format)
- EZMeetup software/App - 30-day for free trial - Connect with H.264 video codec - Receive resolution up to full HD 1080p at 30fps - Transmit resolution up to full HD 1080p at 30fps - Support content sharing, capture and recording
- EZDraw App - Import .JPG, .PNG, .GIF and .BMP files - Export .PNG files - A maximum of 10 devices can be connected
- Dual monitor support
- Speed dialing via hot keys (10 sets)
- Camera presets (100 positions)
- Firmware update via USB flash drive
- Screensaver and auto power off mode
- Network Time Protocol (NTP)
- SnapShot
- Group calling
- Supports SIP voice calls
- ScreenShare software
- VCLink software
- Side by Side of dual camera image
- iSCSI storage device settings

Power supply

- AC 100V ~240V, 50/60Hz
- Consumption: EIAJ 12V, 6.25A

Environmental data

- Operation temperature: 0 ~40°C
- Operation humidity: 20% ~80%
- Storage temperature: -20 ~60°C
- Storage humidity: 20% ~80%

AVer SVC-100-10 Orbit 10 Point MCU,H.323/SIP/SfB. 1080p60 12X PTZ camera, Streaming, Recording, upgradable to 16 points

Physical characteristics

- Package dimensions: 422 x 336 x 374mm
- Package weight: 8.88kg
- Main system (codec): 320 x 267.4 x 37.3mm
- eCam PTZ III: 205 x 205 x 195mm
- SVC microphone array: 144.8 x 128.45 x 27.8mm

Optional accessories

- Additional microphone
- Camera mount
- USB-to-RS232 converter

License options

- 2,4,6,8,10 multipoint license for up to maximum 16 sites

Warranty

- 3+2 year warranty* * Please register online to receive free 2 year warranty extension. For detailed warranty information, please contact an AVer representative. ** Built-in 32G recording storage capacity (actual formatted capacity may be less).

Please Enquire
