

AVer CAM530 PTZ Camere with HDMI & USB, optical zoom: 12X, 1080p@60fps max, color: black



Product Name: AVer CAM530 PTZ Camere with HDMI & USB, optical zoom: 12X, 1080p@60fps max, color: black
Manufacturer: -
Model Number: 61V8U00000BK

Please Note: This product is no longer available. To find an alternative, please see our IP Video Conferencing solutions.

AVer CAM530 PTZ Camere with HDMI & USB, optical zoom: 12X, 1080p@60fps max, color: black

The AVer CAM530 is designed to meet the unified communications and collaboration needs of a variety of businesses. Widely compatible and ideal for numerous applications and integration with other equipment, its full HD 1080p 60fps capability ensure high-quality real-time communication whether in conference rooms or industrial environments. Moreover, CAM530 provides both a USB and HDMI connection, perfect for software- or cloud-based video collaboration and other applications that require very high quality video.

AVer CAM530 Key Features

- Full HD 1080p 60fps
- Pan: $\pm 130^\circ$; 0.45° step
- Tilt: $+90^\circ/-25^\circ$; 0.25° step
- Field of view (H): 72.5° (wide) $\sim 6.3^\circ$ (tele)
- Sensor: 1/2.8 low lux CMOS 2M pixel
- Resolution: full HD 1080p (1920x1080), HD 720p (1280x720), PAL (1024x576), VGA (640x480), QVGA (320x240), QQVGA (160x120) at 60fps, 30fps and 15fps
- Scan: progressive
- Zoom: 18X total zoom (12X optical zoom)
- Lens focal length: 3.9mm (wide) ~ 47.3 mm (tele)
- Lens F#: 1.8 (wide) ~ 2.8 (tele)
- Auto Iris
- S/N ratio: > 50 dB
- Minimum illumination: 1 lx (50 IRE, F1.6, shutter 1/30)
- 2D and 3D denoise
- Backlight compensation
- Flip, mirror
- Minimum working distance: 1.5 meter
- Include table/wall/ceiling mount
- Kensington slot

AVer CAM530 - Technical Specifications

Package contents

- Camera
- Remote control
- 5m USB cable to PC (USB2.0 mini B to PC)
- Power supply
- Quick-start guide
- Tabletop/wall/ceiling mount
- 6.35mm tripod mounting screw
- Velcro

AVer CAM530 PTZ Camere with HDMI & USB, optical zoom: 12X, 1080p@60fps max, color: black

- 3m HDMI cable
- RS232 adapter

System requirements*

- Windows®; 7/ 8/8.1/10
- Mac OS®; X 10.7 or higher
- Google Chromebook version 29.0.1547.70, Platform 4319.79.0

Environmental data

- Physical characteristics: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

Camera

- Full HD 1080p 60fps
- Pan: ±130°; 0.45°/step
- Tilt: +90°/-25°; 0.25°/step
- Field of view (H): 72.5° (wide) ~ 6.3° (tele)
- Sensor: 1/2.8 low lux CMOS 2M pixel
- Resolution: full HD 1080p (1920x1080), HD 720p (1280x720), PAL (1024x576), VGA (640x480), QVGA (320x240), QQVGA (160x120) at 60fps, 30fps and 15fps
- Scan: progressive
- Zoom: 18X total zoom (12X optical zoom)
- Lens focal length: 3.9mm (wide) ~ 47.3mm (tele)
- Lens F#: 1.8 (wide) ~ 2.8 (tele)
- Auto Iris
- S/N ratio: >50dB
- Minimum illumination: 1 lx (50 IRE, F1.6, shutter 1/30)
- 2D and 3D denoise
- Backlight compensation
- Flip, mirror
- Minimum working distance: 1.5 meter
- Include table/wall/ceiling mount
- Kensington slot

Hardware requirements*

- 2.4 GHz Intel®; Core 2 Duo processor
- 2 GB RAM or more
- Hard drive space for recorded videos
- USB 2.0 port

Physical characteristics

- Package dimensions: 370 x 252 x 275mm
- Package weight: 4.16kg/9.17lbs
- Camera: 180 x 140 x 182mm/1.5kg
- Remote control: 200 x 50 x 20mm/0.091kg

AVer CAM530 PTZ Camere with HDMI & USB, optical zoom: 12X, 1080p@60fps max, color: black

Warranty**

- 3-year: camera
- 1-year: accessories

Remote control

- IR (Infrared)
- 10 camera presets (100 presets via VISCA)

Power supply

- AC 100V ~ 240V
- Consumption: EIAJ 12, 4A

Compliance and tools

- YUV, MJPEG, H.264 SVC, AVC (high and base profile)
- Multi-stream capable
- USB 2.0
- UVC (USB Video Class) 1.1 with H.264 extension
- VISCA via RS232*
- HDMI 1.3
- DIP Switch
- Downloadable diagnostic tool, field firmware upgrade tool, App for advanced features and settings

*Please check AVer product web page for compatible VISCA commands and devices.

Please Enquire
