

## Yealink W60 DECT IP Phone Package



Product Name: Yealink W60 DECT IP Phone Package

Manufacturer: -

Model Number: W60P

Please Note: This product is end of life. For an alternative, see the Yealink W76P.

### Yealink W60 DECT IP Phone Package

The Yealink W60, being a high-performance SIP cordless phone system, is the ideal solution for small and medium-sized businesses. Paring with up to a total of 8 Yealink W52H/W56H DECT handsets, it allows you enjoy superb mobility and flexibility.

#### Yealink W60 Key Features

- High-performance SIP cordless phone system
- Up to 8 concurrent calls
- Up to 8 DECT cordless handsets
- Up to 8 VoIP accounts
- Up to 30-hour talk time and 400-hour standby time
- Noise Reduction System

By supporting Opus codec, W60 Package consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions. Offering the convenience of cordless with a simple add-on device without losing the SIP features, it brings a seamless call management for users while "on-the-go".

The Yealink DECT IP phone W60 Package supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism, saving time and additional costs.

#### Yealink W60 - Technical Specifications Phone Features

- Up to 8 simultaneous calls
- Up to 8 handsets
- Up to 8 VoIP accounts
- Up to 2 simultaneous calls per handset
- Up to 5 repeaters per base station
- Handset selection for receiving call
- Handset and number selection for placing call
- Paging, intercom, auto answer, dial plan
- Call hold, call transfer, 3-way conference
- Switching between calls
- Call waiting, mute, silence, DND
- Caller ID with name and number
- Anonymous call, Anonymous call rejection
- Call forward (always/busy/no answer)
- Speed dial, voicemail, redial
- Message Waiting Indication (MWI)
- Local phonebook for up to 500 entries (store in the base)
- Remote phonebook/LDAP
- Phonebook search/import/export
- Call history (all/missed/placed/received)
- Direct IP call without SIP proxy
- Reset to factory, reboot
- Keypad lock, emergency call, music on hold
- Broadsoft directory, BroadSoft call log

## Yealink W60 DECT IP Phone Package

- Broadworks feature key synchronisation
- Shared Call Appearance (SCA)

### Personalisation

- 9 ringer melodies
- Screen saver
- Multilingual user interface

### Management

- Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- Auto-provision with PnP
- Handset upgrade: OTA (Over-The-Air)/USB port
- Configuration: browser/phone/auto-provision
- Trace package and system log export

### Audio Features

- Full-duplex speakerphone
- Hearing Aid Compatibility (HAC) compliant
- Receiver volume control: 5 steps
- Ringer volume control: 5 steps+off
- Multiple advisory tones
- Acoustic warning for low battery status
- DTMF
- Wideband codec: Opus, AMR-WB (optional), G.722
- Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
- VAD, CNG, AEC, AGC, PLC, AJB
- Support VQ-RTCPXR (RFC6035)

### Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SNTP/NTP
- VLAN (802.1Q and 802.1P)
- 802.1x, LLDP, PPPoE
- STUN Client (NAT Traversal)
- UDP/TCP/TLS
- IP assignment: static/DHCP
- Support outbound proxy server backup

### Security

- Open VPN
- Transport Layer Security (TLS)
- HTTPS (server/client), SRTP (RFC3711)
- Digest authentication using MD5
- Secure configuration file via AES encryption
- Support SHA256/SHA512/SHA384
- Three-level configuration mode: Admin/Var/User

### DECT

- Frequency bands: 1880 &ndash; 1900 MHz (Europe), 1920 &ndash; 1930 MHz (US)

## Yealink W60 DECT IP Phone Package

• DECT Standards: CAT-iq2.0

### Interface

- 1 x RJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af), Class 1
- Headset jack (3.5 mm)

### Physical Features

- Indoor Range: 20m~50m (The ideal distance is 50m)
- Outdoor Range: 300m (in ideal conditions)
- Standby Time: 400 hours (in ideal conditions)
- Talk Time: 30 hours
- 2.4" 240x320 pixels color display
- Desktop or wall mountable
- LCD backlit, key backlit
- Energy-saving ECO mode/ECO Mode+
- 12 key numerical keypad, 5 navigation keys, 2 softkeys, 6 function keys, 6 shortcut keys
- Three LED indicators on W60B: 1 x Registration LED 1 x Network Status LED 1 x Power Indicator LED
- External Yealink AC adapter AC 100-240V Input and DC 5V/600mA Output
- Phone size: 175mm x 53mm x 20.3mm
- Base station size: 130mm x 100mm x 25.1mm
- Operating humidity: 10~95%
- Operating temperature: 10~+50°C (+14~122°F)

### Package Features

- Package content: W56H Handset-W60B Base Station-Base Stand-USB Charger Cradle-Two Power Adapters-Ethernet Cable-Belt Clip-Rechargeable Battery-Quick Start Guide
- Qty/CNT: 10 PCS
- Giftbox size: 205mm\*196mm\*95mm
- Carton meas: 495mm\*406mm\*223mm
- N.W: 7.5 kg
- G.W: 8.3 kg

**Price: £0.00**

Options available for Yealink W60 DECT IP Phone Package :

### Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Not Required, Required - 30 minutes (+£40.00).

### Additional Handset

Not Required, Yealink W56H Additional DECT Handset (+£56.00).