



RTX 4022 PRO DECT Repeater

-		

Product Name: RTX 4022 PRO DECT Repeater Manufacturer: -Model Number: RTX4022P

Please Note: This product is no longer available. Please see the RTX DECT Repeaters & amp; IP Phones section for alternative products.

RTX 4022 PRO DECT Repeater A RTX 4022 PRO DECT Repeater can be deployed when a need to extend the range of a DECT telephone arises. The repeater can also be utilised wherever there is a need to increase limited coverage or improve reception in remote areas.

RTX 4022 PRO DECT Repeater Key Features

ï¿1/2 Supports automatic handover of calls between cells

- \ddot{i}_{2} Up to 6 repeaters per base station
- ï¿1/2 Handling of 2 active calls simultaneously
- ï¿1/2 Repeater-to-repeater registration, max. 3 repeaters in daisy chain
- ï¿¹/₂ Dedicated programming key
- ï¿1/2 2 internal antennas
- ï¿1/2 Suitable for wall mounting

RTX 4022 PRO DECT Repeater - Technical Specifications General

ï¿1/2 Worldwide DECT support

- ï¿1/2 Extending the DECT coverage
- � Supports automatic handover of calls between cells
- ï¿1/2 Handling of 2 active calls simultaneously
- ï¿1/2 Up to 6 repeaters per base station
- ï¿¹/₂ Automatic registration method
- ï¿1/2 Environmental conditions: temp range, from -10°C to +50°C

Design/Size

ïز½ Indoor cabinet ïز½ Manual mounting kit ïز½ Easily mounted on walls

ï¿1/2 Size: 120(W) x 35(D) x 135(H)mm

Power Supply

ï¿1/2 230 VAC and 110 VAC versions available

Frequency/Coverage

ï¿1/2 Frequency bands coverage: EU/AU/NZ, US/CA, LATAM, TW

 $\ddot{\imath}_{\mathcal{E}}^{1\!\!/_{\!\!2}}$ Up to 50m indoor and 300m outdoor

ï¿1/2 Receiver sensitivity: -92dBm

ï¿1/2 2 internal omni-directional antennas

Standards/Approvals

ïزائ The DECT repeater is designed in accordance with the Digital Enhanced Cordless



RTX 4022 PRO DECT Repeater

Telecommunications (DECT) standard � The DECT repeater is compliant with:- TBR6, TBR22 (Generic Access Profile, GAP)- ETS 300 700 - ETSI Wireless Relay Station Specification

LED Indicator

ï¿1/2 Radio link quality indication

Additional Features

 \ddot{i}_{2} Repeater to repeater registration (max. 3 repeaters in daisy chain) \ddot{i}_{2} Requires a PC tool which can be delivered by RTX

Please Enquire