

DrayTek VigorSwitch VSP2121-K 8 Port Gigabit Switch



Product Name: DrayTek VigorSwitch VSP2121-K 8 Port Gigabit Switch

Manufacturer: -

Model Number: VSP2121-K

Please Note: This product has been discontinued. Please see the Draytek VigorSwitch VSP2100-K.

DrayTek VigorSwitch VSP2121-K 8 Port Gigabit Switch

The DrayTek VigorSwitch VSP2121-K is an 8 port Gigbit switch featuring Draytek's own operating system. It has advanced features such as IPv4 and IPv6 support as well as features for Quality of Service (QoS), VLANs and network/switch.

DrayTek VigorSwitch VSP2121-K Key Features

� 8+4 Port Gigabit Managed Switch:

ï¿1/2 8 x RJ-45 Ethernet Ports with PoE+

تزارط 4 x Combo RJ-45 or SFP (Fibre Module) Ports

าั¿½ PoE (Power-over-Ethernet) for IP phones, wireless access points, IP Cameras etc.

� Fanless for silent operation with generous 140w PoE Power budget

i¿½ 802.3af (PoE) and 802.3at (High Power PoE)

� 802.1q VLANs (Tag, Port & MAC-based)

ï¿1/2 Access Control List (ACL)

าั¿½ Secure Networking with 802.1x Port Security, IP Source Guard and DHCP Snooping

� QoS for Application traffic prioritisation

آذا Voice & De Camera VLANs for auto QoS prioritisation via MAC address OUI

� Port Mirroring & Eink Aggregation

าั¿½ IGMP Snooping/Querier and IPv6 MLD Snooping

� IPv4 and IPv6 Support

� Centrally managed or standalone operation

� Console Port for CLI configuration

� Desktop, Wall or Rack mountable

DrayTek VigorSwitch VSP2121-K Technical Specifications

Physical Interfaces:

� 8 10/100/1000BaseT Ethernet Ports (RJ-45 IEEE 802.3/3u/ab)

� 4 Selectable Ports (Nos. 9-12), use as either:

آذِرُ 10/100/1000BaseT (Gigabit) Ethernet

� SFP (802.3z)

า๊¿½ Console Port (RJ-45 physical, RS-232 electrical)

PoE Specification

าั¿½ 8-ports 802.3af & amp; 802.3at (High Power) PoE PSE

� 140 Watts Total Power Budget for PoE

ī¿½ Auto Detection of Powered Device (PD) and Consumption Levels



DrayTek VigorSwitch VSP2121-K 8 Port Gigabit Switch

- � PoE Status LED Indicators
- า๊¿1/2 Supports per Port Power Consumption Monitoring
- � PoE PD Scheduling (per port)
- � PoE PD Priority (per port)
- ī సై PoE PD Status / Ping monitoring restart PoE PD port on no connectivity (per port)
- � Circuit Protection to Prevent Power Interference between Ports

VLAN:

- ï¿1/2 802.1q Tag-based VLAN
- ï¿1/2 Port-based and MAC-based VLANs
- � QinQ (Basic)
- i¿½ GVRP (General VLAN Registration Protocol)
- آزٰ Up to 4K VLANs (out of 4096 VLAN IDs)
- � 802.1v Protocol-Based VLAN
- � Voice VLAN (OUI Mode)
- � Surveillance VLAN (OUI Mode)
- آز½ Protocol VLAN
- ï¿⅓ MAC-based VLAN
- ï¿1/2 Management VLAN

QoS

- ï¿⅓ Support 8 priority queues
- � Port-Based rate control
- آذِ 1/2 Priority queue schedule (WRR or Strict Priority)
- � Class of Service
- ï¿1/2 802.1p CoS
- � DSCP
- � CoS-DSCP
- ï¿⅓ IP Precedence ToS

Network Security

- ï¿1/2 Access Control Lists (ACL)
- ï¿1/2 Source and destination MAC
- آز½ VLAN ID
- ï¿1/2 IPv4/v6 address
- ï¿⅓ Protocol
- � TCP/UDP port
- آزٰ½ Up to 512 entries
- ï¿⅓ IP Source Guard
- រ៉េ¿½ Storm Control (Broadcast, Unknown Multicast, Unknown Unicast)
- � DoS Attack protection
- ï¿1/2 AAA Authentication
- ï¿⅓ MAC Authentication
- � Protected Port / Port Isolation
- � Static Port Security
- � Dynamic ARP Inspection
- � DHCP Snooping with Option 82

Link Aggregation



DrayTek VigorSwitch VSP2121-K 8 Port Gigabit Switch

- i¿1/2 Combine multiple ports to increase bandwidth
- ï¿1/2 8 Aggregation Groups
- � Up to 8 ports in each group
- ï¿1/2 LACP or Static setup
- ï¿⅓ Supports traffic load balancing

Networking Performance

- ï¿⅓ Switching Capacity: 24Gbps
- � Forwarding Rate: 17.8Mpps
- ï¿1/2 MAC Addresses Supported: 8K
- ï¿1/2 Jumbo Frames up to 9KB

Multicast

- ï¿1/2 Up to 256 multicast groups
- ï¿1/2 IGMP Snooping V2/V3 (BISS)
- ï¿1/2 IGMP V2/V3 Querier
- آزٰ Filtering / Throttling
- ï¿1/2 MLD Snooping V1/V2
- ï¿⅓ Immediate Leave
- ï¿⅓ Multicase VLAN registration

AAA

- ï¿1/2 802.1x Single / Multiple
- � Port based
- ï¿⅓ Mac Based
- ï¿⅓ Guest VLAN
- آذِا External AAA server using RADIUS / TACACS

Management

- ï¿1/2 IPv4 & IPv6 Dual-Stack
- � LLDP(802.1ab) + MED
- آزٰ Web User Interface (HTTP or HTTPS)
- า๊ะ/2 Firmware Upgrade/Backup by HTTP/HTTPS
- 12/2 HTTP (Non-TLS) can be disabled for increased security
- � Configuration Backup/Restore
- ï¿⅓ Factory Default
- ï¿1/2 System Reboot
- آذِرُ Dual Firmware Image (Active & Errmware)
- � Command Line Interface (CLI) via SSH/Telnet
- � Console Port (RJ45) for CLI management
- īస్ట్ DrayTek Switch Management support via router (requires router firmware support)
- � VigorACS Compatible (TR-069)
- تز1/2 SNMP v1, v2c, v3 (with Generic Traps)
- آذِرُ RMON Groups 1, 2, 3, 9 (History, Statistics, Alarms, Events)

Diagnostics



ï¿1/2 Port Status & amp; Usage display

� PoE active display

� CPU/RAM Usage display

� Event Log

ï¿⅓ Port Mirroring

ï¿⅓ Ping

� Port-based cable test

General IEEE Standards Compliance:

ï¿1/2 802.3 10Base-T

ï¿1/2 802.3u 100Base-T

ï¿1/2 802.3ab 1000Base-T

ï¿1/2 802.3x Flow Control Capability

� 802.3 Auto-negotiation

� 802.1Q VLAN

ï¿1/2 802.1p Class of Service

� 802.1d Spanning Tree

ï¿1/2 802.1w Rapid Spanning Tree

ï¿1/2 802.1s Multiple Spanning Tree

تزا 802.1x Port Based Network Access Control

i¿½ 802.1ab Link Layer Discovery Protocol (LLDP)

ï¿1/2 802.3ad Port trunk with LACP

� 802.3az Energy Efficient Ethernet

� 802.3af PoE

� 802.3at PoE+

Operating Requirements:

ï¿1/2 Power Input Requirements: 220-240VAC

� Power supply: Internal

า๊¿½ Maximum Input Power Consumption: 164 Watts

� Operating Temperature: ~0°C to ~40°C

า๊ะ่½ Storage Temperature: -20°C to ~70°C

آذًا 2 Operating Humidity: 10% to 90% RH (non-condensing)

Physical Specifications:

� Dimensions (W x D x H): 330 x 230 x 44 mm

� Weight: 2.43Kg (excluding SFP modules/cables)

ï¿1/2 Brackets included for rack or wall mounting

� Rack mountable: 1U

ROHS & amp; CE Compliant

Price: £192.00