

2N IP Solo Flush Mount in Brushed Nickel 9155301CF (requires 9155017 for installation)



Product Name: 2N IP Solo Flush Mount in Brushed Nickel 9155301CF (requires 9155017 for installation)

Manufacturer: 2N Telecommunications

Model Number: 9155301CF

2N IP Solo Flush Mount in Brushed Nickel 9155301CF (requires 9155017 for installation)

The 2N IP Solo Flush Mount in Brushed Nickel 9155301CF is a great addition to any smart home. Despite only having one button, it will nonetheless astonish you with its many functions, including calls to your smart phone as well as easy integration into existing home automation systems. The 9155301CF is manufactured as a stand-alone unit and includes 1 camera with night vision, built-in microphone, 1 button and 1 flush mount frame.

2N IP 9155301CF Features

- Stylish addition to any Smart Home security system
- Sharp video day and night
- Stylish and durable
- Camera with night vision
- Easy integration into the home automation system
- Picture to email
- Must be used in conjunction with flush mount installation Mounting Box 9155017 (not included)
- Calls to mobile phone or tablet
- Integrated microphone and 2W / 8Ω speaker
- Finished in brushed Nickel

2N IP 9155301CF - Technical Specifications

General

- Signalling protocol: SIP 2.0 (RFC - 3261)
- Buttons: 1 x Transparent buttons with white backlight and easily removable label
- Microphone: 1 built-in microphone
- Speaker: 2W (Sound pressure at 1 kHz at 1 m distance)
- Codecs: G.711, G.722, G.729, L16/16kHz
- Camera resolution (JPEG): 1280 x 960 px
- Camera resolution (video call): 640 x 480 px
- Viewing angle: 120° (H), 90° (V), 145° (D)
- Night vision: Yes
- Video codecs: H.263+, H.263, H.264, MJPEG
- LAN 10/100BaseTX with Auto MDIX
- Relay Outputs NC/NO contacts, max 30v/1A AC/DC
- Power supply: 12v ±15% / 2A DC or PoE
- PoE: PoE 802.3af (Class 0 - 12.95W)
- LAN: Screw-in connector, 10/100BASE-TX with Auto-MDIX
- Supported protocols: SIP2.0, DHCP opt. 66, ONVIF, SMTP, 802.1x, RTSP, RTP, TFTP, HTTP, HTTPS, Syslog
- Operating temperature: -40°C to 60°C (expected value, hasn't been confirmed yet)
- Ingress protection: IP54
- Vandal protection: IK08
- Finish: Nickel
- Dimensions: 130(W) x 153(H) x 5(D) mm
- Weight (Net): 1.00kg
- Weight (Gross): 1.00kg

2N IP Solo Flush Mount in Brushed Nickel 9155301CF
(requires 9155017 for installation)

Price: £852.60
