

JPL Connect VoIP Headset (JPL-CONNECT-2)



Product Name: JPL Connect VoIP Headset (JPL-CONNECT-2)

Manufacturer: -

Model Number: JPL-CONNECT-2

Please Note: This product has been discontinued. Please see the JPL 611 VoIP Headset (JPL-611-PB).

JPL Connect VoIP Headset (JPL-CONNECT-2)

The JPL Connect 2 is a super light-weight affordable professional office and contact centre headset suitable for regular phone users.

JPL Connect 2 Key Features

- 121/2 Single and dual ear options available
- � Left / right ear side compatible
- � Ideal for all-day comfort
- � Weighted filter for clearer Surround Shield ultra noise cancelling
- � Wideband enabled speakers
- � Strong, robust construction
- ī¿½ Fitted with large 70mm leatherette ear cushions for maximum all-day comfort
- าั¿1/2 Optional 50mm leatherette ear cushions included
- ï¿1/2 Adjustable headband
- � 'Put and stay' ratchet microphone boom arm
- าั¿½ Supplied with quick disconnect system(QD) QD compatible with Plantronics
- ī¿½ Headset weight with the 70mm ear cushions, ~ 62g / ~102g
- � Protective hard-shell carry case included
- � Clothing clip & mp; hanging hook included
- � Compatible with all known office phones
- � Full range of bottom leads available
- � 24 Month repair or replacement warranty

JPL Connect 2 Technical Specifications Microphone

- ï¿1/2 Impedance: Max. 2.2KΩ
- ï¿1/2 Sensitivity: -32dB ± 3dB at 1kHz
- � Directivity: Bi-directional
- ï¿1/2 FrequencyRange: 50Hz~20kHz ± 6dB
- � Distortion: Less than 3%� Power Supply: 3V DC� S/N Ratio: More than 58dB

Speaker

- ī¿½ Impedance: 150Ω ± 15% at 1kHz ī¿½ Sensitivity: 93 ± 3dB at 1kHz 60mV Input
- � Max Input Power: 100mV
- � Frequency Range: 100Hz~6800Hz � Distortion: Less 3% at 1kHz 60mV

Agency Approvals

� RoHS, CE, FCC



JPL Connect VoIP Headset (JPL-CONNECT-2)

Please Enquire

Options available for JPL Connect VoIP Headset (JPL-CONNECT-2):

Disconnect Cord Required?

BL04-P (Sangoma, Snom, Yealink, Grandstream) (+£5.45), Not Required, BL-054MS-P (Softphone) (+£24.00), BL01-P (Fanvil) (+£5.45).