

Yeastar TG400 VoIP GSM Gateway 4 GM1



Product Name: Yeastar TG400 VoIP GSM Gateway 4 GM1

Manufacturer: Yeastar

Model Number: TG400G

Yeastar TG400 VoIP GSM Gateway

The Yeastar TG400 connects GSM to VoIP networks to provide two-way communication: GSM to VoIP and VoIP to GSM.

Yeastar TG400 Key Features

- 1/2 GSM Voice Calls
- 1/2 Maximum Cost Reduction
- 1/2 Top Quality and Reliability
- 1/2 Mobile Connectivity for SMB

It allows you to connect most IP-based telephone systems including Yeastar IP Phone Systems, and softswitches to a GSM which can provide a sophisticated fallback solution when landlines go down, or be used to increase call traffic capacity by providing additional dial-tone. Easy to use Simple and intuitive Web-based configuration saves you loads of time

Mobile Trunkings

Add GSM/WCDMA trunkings for business making high number of calls to mobile networks

Bulk SMS Service

Great tool for enterprises to manage customer relations and introduce special offers with a low cost

Interoperability

Interoperable with a broad list of softswitch, PBX, and IP-PBX like Elastix and Lync Server

Yeastar TG400 Technical Specifications

Interface

• 1/2 TG400: 4 GSM

• 1/2 TG100, TG200, TG400: 1 10/100 Mbps Ethernet Interface

Voice Processing

• 1/2 Protocol: SIP, IAX2

• 1/2 Transport: UDP, TCP, TLS, SRTP

• 1/2 Voice Codec: G.711 (alaw/ulaw), G.722, G.726, G.729A, GSM, ADPCM, Speex

• 1/2 Echo Cancellation: ITU-T G.168 LEC

• 1/2 DTMF Mode: RFC2833, SIP INFO, In-band

• 1/2 SIP Server for IP Phones Included

• 1/2 SIP Response Code Switch

• 1/2 Call Progress Tone Generation

• 1/2 1 Stage/2 Stage Dial

System Features

• 1/2 Mobile Ports Groups

• 1/2 VoIP Trunk Group

• 1/2 Incoming /Outgoing Routing rules

• 1/2 Black List

• 1/2 Hotline

• 1/2 AutoCLIP

• 1/2 Call Duration Limitation

• 1/2 Call Transfer

• 1/2 Call Back

Yeastar TG400 VoIP GSM Gateway 4 GM1

- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

System Features

- Mobile Ports Groups
- VoIP Trunk Group
- Incoming /Outgoing Routing rules
- Black List
- Hotline
- AutoCLIP
- Call Duration Limitation
- Call Transfer
- Call Back
- Call Detail Record (CDR)
- Call Status Display
- NTP
- IP Blacklist
- Network Attack Alert
- Packet Capture
- System Logs

Mobile Features

- GSM Frequency: 850/900/1800/1900MHz
- WCDMA Frequency: 850/1900MHz, 850/2100MHz, 900/2100MHz
- SMS Sending and Receiving
- Send Bulk SMS
- SMS Center
- Gain Adjustment
- USSD
- PIN Modify
- Carrier Selection: Auto/Manual
- Talk Time Alarm
- Caller ID/CLIR
- Open API for SMS and USSD

Network & Management

- Network Protocol: FTP, TFTP, HTTP, SSH
- NAT Traversal: Static NAT, STUN
- Static Route
- OpenVPN
- Firewall
- VLAN
- QoS/ToS
- DDNS
- Configure Backup/Restore
- Firmware Upgrade by HTTP/TFTP
- Web based Configuration

Yeastar TG400 VoIP GSM Gateway 4 GM1

Physical

Size (mm): 213x160x44

Power Supply: AC 100-240V

Price: £666.70
