

Cyberdata 011491 SIP Outdoor Call Button



Product Name: Cyberdata 011491 SIP Outdoor Call Button

Manufacturer: CyberData

Model Number: 011491

Cyberdata 011491 SIP Outdoor Call Button

The Cyberdata 011491 is a reliable solution for a one-touch programmable call to an IP phone or page announcement. This IP66 rated device can be mounted on an outside wall, external door, parking area, or harsh environment. If an event occurs, only a simple button press is required to automatically place a call to the configured phone or extension number. When the called number answers, the Call Button plays and repeats a stored audio file. This stored audio file is uploaded by the administrator to meet the needs of the installed location

Cyberdata 011491 Key Features

- TLS 1.2 enhanced security for IP Endpoints in a local or cloud-based environment
- Supports SRST (Survivable Remote Site Telephony) in a Cisco environment
- Network web management and firmware download
- Dry relay contact for auxiliary control
- Door closure and tamper alert signal
- User downloadable message up to 80 seconds
- Single button call to pre-set number
- Continuous repeat of message
- Call progress light

In a Singlewire InformaCast environment, the SIP Outdoor Call Button registers to the Cisco Call Manager as a third party SIP endpoint. When the Call Button is depressed it makes a call to the Cisco Call Manager and the Singlewire InformaCast software detects that call and initiates an event. CyberData has maintained one of the most comprehensive lists of IP PBX servers certified to work with CyberData VoIP Products.

Cyberdata 011491 Technical Specifications

General

- Ethernet: 10/100 Mbps
- Protocol: SIP RFC 3261 Compatible
- Power Input: PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
- On-Board Relay: 1A @ 30 VDC
- Payload Types: G.711 a-law, G.711µ-law, G.722, and G.729
- Network Security: TLS/SSL 1.2
- IP Rating: IP66
- Operating Range: Temperature: -40 degrees C to 55 degrees C (-40 degrees F to 131 degrees F) Humidity: 5-95%, non-condensing
- Storage Range: -40 degrees C to 70 degrees C (-40 degrees F to 158 degrees F)
- Storage Altitude: Up to 15,000 ft. (4573 m)
- Dimensions: 5.1 inches [129.5 mm] Length, 2.4 inches [61 mm] Width, 5.1 inches [129.5 mm] Height
- Weight: 2.0 lbs. (0.90 kg)
- Boxed weight: 3.0 lbs. (1.35) kg)
- Warranty: 2 years limited
- Compliance: CE; EMC Directive & Class A EN 55032 & EN 55024, LV Safety Directive & EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
- Part Number: 011491

Cyberdata 011491 SIP Outdoor Call Button

Price: £507.50
