

Polycom VVX EM50 Expansion Module



Product Name: Polycom VVX EM50 Expansion Module

Manufacturer: Polycom / Poly

Model Number: 2200-48890-025

Polycom VVX EM50 Expansion Module

The Polycom VVX EM50 is easy to install and designed exclusively for the Polycom VVX 450 business IP phone. It's an optimal solution for telephone attendants, receptionists, administrative staff and other power users who manage multiple workflows or simultaneous calls on a daily basis.

Polycom VVX EM50 Features

- High Resolution 5.0" Screen
- Multifunctional Line Keys
- Ease of Installation
- Increase Productivity
- Leverage Previous IT Infrastructure Investment
- High Performance Attendant Console
- Plug-and-play Device
- Intuitive User Interface
- Ultimate UC Communications Experience

Polycom VVX EM50 Technical Specification

Display

- 5.0in LCD WVGA (480x800 pixel) resolution
- Colour TFT graphical user interface

Feature Keys

- 30 multifunctional line keys configurable as line registration, call appearance, speed dial, DSS or BLF
- Dual-color (red or green) illuminated LEDs for line status information
- 3-page keys for additional line appearances

Compatible VVX Phone Models

- VVX 450
- Communication with host phone and/or other modules via USB port

Expandability

- Up to two Expansion Modules can be attached to the VVX 450

Feature Support

- Additional line registrations
- Shared call appearance, bridged line appearance (key system emulation)
- Call transfer
- Busy lamp field
- Speed dial
- Fully programmable line appearances
- Multilingual user interface (driven from host phone)
- Skype for Business presence

Polycom VVX EM50 Expansion Module

Power

- Provided by Polycom VVX host phone
- Host phone powering options: IEEE 802.3(af/at) PoE or using an approved compatible external AC adapter (5VDC/3A)
- Powering starts automatically upon USB port connection
- No additional power source is required

Approvals

- FCC Part 15 (CFR 47)
- ICES-003
- CE Mark
- VCCI
- RCM
- Russia CU
- ROHS-compliant

Safety

- UL 60950-1/62368-1
- CAN/CSA-C22.2 No. 60950-1/62368-1
- EN 60950-1/62368-1
- IEC 60950-1/62368-1
- AS/NZS 60950-1

Operating Conditions

- Temperature: 0 to 40 degrees C (+32 to 104 degrees F)
- Relative humidity: 5% to 95%, noncondensing

Storage Temperature

- -40 to +70 degrees C (-40 to +160 degrees F)

VVX EM50 comes with:

- VVX EM50 console
- VVX EM50 desk stand
- Interconnection bracket and screws
- Setup sheet

Dimensions

- 12.5 x 12.5 x 16 x 6 cm (5 x 5 x 6.5 x 2.5 in) (WxHxDxT)

Weight

- Shipping: 0.5kg (1lb)

Unit Box Dimensions/Weight

- 11 x 6 x 3.5 in/0.7 kg

Unit Box

Polycom VVX EM50 Expansion Module

1/2 213 x 161 x 72 mm (8.4 x 6.3 x 2.8 in)

Overpack Box

1/2 648 x 369 x 223 mm (25.5 x. 14.5 x 8.8 in)

Country of Origin

1/2 Laos

Warranty

1/2 One (1) year

Price: £171.70
