CyberData InformaCast Enabled Wall Mount Speaker (011505)

Product Name: CyberData InformaCast Enabled Wall Mount Speaker (011505)
Manufacturer: CyberData
Model Number: 011505

CyberData InformaCast Enabled Wall Mount Speaker (011505)
The CyberData InformaCast Enabled Wall Mount Speaker (011505) is an economical Power-over-Ethernet (PoE 802.3af) and VoIP public address product that plays InformaCast and multicast messages. The speaker will easily connect to your PoE network with a single Ethernet cable. The speaker's streamlined case and mounting hardware offers an easy installation in almost any environment.
 CyberData InformaCast Enabled Wall Mount Speaker (011505) Key Features

ï¿½ User upgradeable firmware via web interface or autoprovisioning
ï¿½ Can receive pages directly from Poly phones as well as other devices that can send standard multicast
ï¿½ Capable of receiving Singlewire InformaCast and multicast messages
ï¿½ Supports Singlewire InformaCast High Quality Audio
ï¿½ Supports audio prioritisation for 10 multicast paging groups
ï¿½ Network-adjustable speaker volume
ï¿½ High efficiency speaker driver
ï¿½ Small footprint
ï¿½ TLS security for autoprovisioning and web-based configuration
ï¿½ 802.11q VLAN tagging
ï¿½ Configurable event generation for device health and status monitoring

Typical IP speaker configuration
 CyberData InformaCast Enabled Wall Mount Speaker (011505) Technical Specification
Product Specifications

ï¿½ Ethernet I/F: 10/100 Mbps
ï¿½ Protocol: RTP
ï¿½ Notification Software: Singlewire InformaCast v4.0 and above
ï¿½ Power Input: PoE 802.3af
ï¿½ Audio Output: 802.3af – SPL 98 dB @ 1 meter
ï¿½ Payload Types: G.711 a-law, G.711µ-law, and G.729
ï¿½ Network Security: TLS/SSL 1.2
ï¿½ Operating Range: - Temperature: -40˚ C to 55˚ C (-40˚ F to 131˚ F) - Humidity: 5-95%, non-condensing
ï¿½ Storage Temperature: -40˚ C to 70˚ C (-40˚ F to 158˚ F)
ï¿½ Storage Altitude: Up to 15,000 ft. (4573 m)
ï¿½ Dimensions: - 6.42 in. [163 mm] Length - 5.39 in. [137 mm] Width - 9.18 in. [233 mm] Height
ï¿½ Weight: 3.8 lbs [1.72 kg]
ï¿½ Boxed Weight: 4.4 lbs [1.96 kg
ï¿½ Compliance: CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
ï¿½ Warranty: 2 Years Limited
ï¿½ Part Number: 011505

Price: £373.90