



Product Name: Yealink Cordless DECT IP Multi-Cell Base Station (W80B)

Manufacturer: Yealink Model Number: W80B

Please Note: This product requires the Yealink Cordless IP Multi-Cell DECT Manager (W80DM) to

work.

Please Note: This product is compatible with Zoom.

Yealink Cordless DECT IP Multi-Cell Base Station (W80B)

The Yealink W80B is a DECT IP multi-cell base station that works with the W80BDM DECT Manager to provide organisations with wireless phone system (W80) that's easy to deploy. The Yealink W80 DECT multi-cell system is an extremely scalable and reliable solution for organisations of any size.

Yealink W80B Key Features

ï¿1/2 Seamless handover and roaming

ï¿1/2 Up to 100 parallel calls

آذِ1/2 Up to 30 base stations

� Up to 100 handsets

� Up to 100 SIP accounts

ï¿1/2 Support LDAP/Remote Phonebook

� Support Xsi Directory

าั¿½ DECT radio coverage up to 50m indoors and 300m outdoors

ï¿1/2 Support Opus

ï¿⅓ Support PoE

� Compatible with Yealink W56H/W53H (version x.83.0.20 or later)

The system supports up to 100 handsets and 100 simultaneous calls, this solution not only ensures one call in each handset, but also allows you to get rid of the limited wireless coverage of only one base station. Meanwhile, the system works with Yealink W53H and W56H handsets with seamless roaming and handover of calls, making freely mobile communication in and between each zone achievable. Yealink W80B joins the modern, compact design with Yealink HD voice quality, which is wrapped with the full-duplex technology and Opus, giving you an excellent audio experience.

Security & DECT technology, W80B provides you with both the stable call and the seamless roaming and handover. Wireless data transmission over-the-air is ensured by the DECT encryption. At the same time, TLS and SRTP play a pivotal role in secure SIP communication. Pack Yealink W80B with the powerful Grayscale Upgrade feature, when you perform upgrade for one handset, other handsets are free from this process and the whole system still runs safely.

Advanced DECT ContactsWhen a call is coming, the receiver can obtain the caller information, including the caller number and caller name, from the phone screen easily and clearly. Compatibility with several PBX platforms makes contacts from different platforms reachable on the Yealink W80B e.g. Xsi directory and XML contacts. LDAP and Remote Phonebook are also available on the W80B.

Efficient Provisioning & Efficient Provisioning & Efficient Provisioning & Efficient Provisioning & Efficient Provisioning and effortless mass deployment to be simply implemented via Yealink's Redirection and Provisioning Service (RPS) and auto provisioning. You can also configure and manage the entire multi-cell system on the DECT Manager web portal, making the deployment, maintenance and upgrade trouble-free as well as saving time and IT costs.



Easy Setup and Deployment In the multicast network, administrators profit from zero touch provisioning that the system is established as soon as the base station is powered on and connected to the network. If you are in a non-multicast network environment, obtaining the IP address of the base station from the handset directly helps you set up the system faster and easier. To quickly identify the right position for any of the W80B base stations, try the Yealink Deployment ToolKit.

Yealink W80B - Technical Specifications Phone Features

- ï¿⅓ Sync over the air
- ï¿1/2 Up to 100 simultaneous calls
- ï¿1/2 Up to 30 base stations
- ï¿1/2 Up to 8 WB (4 active handsets) calls per base
- � Up to 8 NB calls per base
- ï¿1/2 Up to 100 handsets
- ï¿1/2 Up to 100 VoIP accounts
- ï¿1/2 Up to 2 simultaneous calls per handset
- � Call hold, call transfer, 3-way conference
- ï¿1/2 Switching between calls
- تز 1/2 Call waiting, mute, silence, DND
- � Caller ID with name and number
- ï¿1/2 Anonymous call, Anonymous call rejection
- � Call forward (always/busy/no answer)
- ï¿⅓ Speed dial, voicemail, redial
- � Message Waiting Indication (MWI)
- ï¿⅓ Music on hold (server-based)
- � Local phonebook for up to 100 entries per handset
- ï¿1/2 Remote phonebook/LDAP
- � Phonebook search/import/export
- ï¿1/2 Call history (all/missed/placed/received)
- � Reset to factory, reboot
- � Keypad lock, emergency call
- � Broadsoft directory, BroadSoft call log
- ï¿1/2 Broadworks feature key synchronisation
- ï¿1/2 Shared Call Appearance (SCA)

Management

- า๊ะ่½ Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- � Auto-provision with PnP
- � Handset upgrade: OTA (Over-The-Air)
- 12.1/2 Configuration: browser/phone/auto-provision
- � Trace package and system log export

Audio Features

- � Full-duplex speakerphone
- ii. 1/2 Hearing Aid Compatibility (HAC) compliant
- Ti2½ DTMF
- i¿1/2 Wideband codec: Opus, AMR-WB (optional), G.722
- 17/2 Narrowband codec: AMR-NB (optional), PCMU, PCMA, G.726, G.729, iLBC
- � VAD, CNG, AGC, PLC, AJB

Network Features



ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)

ï¿⅓ SNTP/NTP

� VLAN (802.1Q and 802.1P)

ï¿1/2 802.1x, LLDP

ï¿1/2 STUN Client (NAT Traversal)

� UDP/TCP/TLS

� IP assignment: static/DHCP

� Support outbound proxy server backup

Security

ï¿⅓ Open VPN

� Transport Layer Security (TLS)

تزر HTTPS (server/client), SRTP

� Digest authentication

17:1/2 Secure configuration file via AES encryption

ï¿1/2 Support SHA256/SHA512/SHA384

DECT

ī¿½ Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)

Interface

� 1 x RJ45 10/100M Ethernet port

� Power over Ethernet (IEEE 802.3af), Class 1

Physical Features

� Indoor Range: 20m~50m (The ideal distance is 50m)

� Outdoor Range: 300m (in ideal conditions)

� Wall mountable

าั¿½ Three LED indicators on W80B: - 1 x DECT LED - 1 x Role LED - 1 x LAN (Power Indicator

& Network Status) LED

� External Yealink AC adapter: AC 100-240V Input and DC 5V/1.2A Output

� Colour: Pearl White

� Dimension: 130 mm x 100 mm x 25.1 mm

� Operating humidity: 10~95%

اتۇ 1 2 Operating temperature: 0~+40°C (+32~104°F)

Package Features

آذِ½ Package content: - W80B Base Station - Expansion Screws - Quick Start Guide - Power Adapter (optional)

� Qty/CNT: 10 PCS

ī¿½ Giftbox size: 174 mm x 180 mm x 63 mm � Carton meas: 375 mm x 336 mm x 187 mm

� N.W: 2.56 kg � G.W: 3.13 kg

Price: £153.90



Options available for Yealink Cordless DECT IP Multi-Cell Base Station (W80B):

Power Supply Required?

Not Required, PSUUK3W (+£3.70).

Need Product Setup / Training / Support?

Not Required, Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00).

DECT Manager Required?

Not Required, Yealink W80DM (+£225.00).