

## Snom D717 Entry-Level IP Phone - White (D717W)



Product Name: Snom D717 Entry-Level IP Phone - White (D717W)

Manufacturer: Snom

Model Number: D717W

### Snom D717 Entry-Level IP Phone - White (D717W)

The Snom D717W is the stylish white version of the D717, featuring an intuitive design with advanced technology and connectivity. Three self-labelling programmable feature keys sit next to a 2.8-inch, 320 x 240 pixel colour LCD display. Opus codec support gives you the freedom to enjoy crystal-clear audio or high-quality narrowband audio, depending on your network conditions.

### Snom D717W Key Features

- Stylish white version
- Integrated ambient light sensor
- Automatic backlight dimming
- Wide screen graphical TFT display
- 3 self-labelling function keys
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port Gigabit Ethernet switch (RJ45)
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset ready
- D7 Expansion Module ready
- Support for USB WiFi stick
- Electronic Hook Switch (EHS) support for wireless headsets
- Dual-angle footstand: 46°; and 28°;

Zero touch provisioning eliminates the need for manual labor typically involved with installation. Power over Ethernet (PoE) support and dual Ethernet ports makes the system cost-effective and easy to use. The USB port allows additional connectivity, including up to three D7 expansion modules for increased visibility and one-button options. The system features multiple configurations, including three programmable feature keys, four soft keys and 14 dedicated feature keys. You'll feel safe with powerful security features like VPN support.

### Snom D717W Technical Specifications

#### Phone Features

- 6 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX Platforms
- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable)

## Snom D717 Entry-Level IP Phone - White (D717W)

- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup
- Call park, call unpark
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)
- Unified Communications ready

### Audio

- Codecs:- G.711 A-law, &mu;-law- G.722 (wideband)- G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

### Setup

- Configurable through web interface
- Provisioning: - Automatic loading of settings via HTTP/HTTPS/TFTP - DHCP Options 66/67
- Snom Redirection Service- Remote management via TR-069 / TR-111

### Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

### User Interface

- Localisation (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context sensitive keys
- 3 programmable line / function keys with multicolour LEDs
- Dedicated keys for: Message, DND, directory, menu, transfer, hold, page
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 5-way navigation key
- OK and cancel keys
- Automatic backlight enabled

### Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)

## Snom D717 Entry-Level IP Phone - White (D717W)

- SRTP (RFC3711), SIPs, RTCP
- HTTPS server/client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

### Phone Features

- Dimensions (approx.): - 205 x 185 x 40 mm (LxWxD) w/o foot stand - 205 x 185 x 200/220 mm (LxWxD) with foot stand
- Weight (approx.): device 710g, footstand 120g
- Input voltage: 5V DC (SELV)
- Power supply: PoE or 5Vdc power adapter, 10 Watts
- Handset: 4P4C
- Headset: 4P4C; Support for Snom EHS Advanced
- Hearing aid compatible (HAC) handset
- 1 x USB 2.0 host port, Type A
- Environmental conditions: - Ambient temperature: 0°C to 35°C (32°F to 95°F) - Storage temperature: -10°C to 45°C (14°F to 113°F) - Humidity: 5% to 95% (non-condensing)
- Included in delivery: - Phone unit - Footstand - Handset with cord - Ethernet cable - Quick Start Guide
- Colour: Black or White

### Type Approvals:

- CE Mark
- Safety IEC 60950

**Price: £80.20**

Options available for Snom D717 Entry-Level IP Phone - White (D717W) :

### Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Not Required, Required - 30 minutes (+£40.00).