

## OpenVox SWG-M204 Wireless Gateway with 4 GSM Channels (SWG-M204G)



Product Name: OpenVox SWG-M204 Wireless Gateway with 4 GSM Channels (SWG-M204G)

Manufacturer: OpenVox

Model Number: SWG-M204G

OpenVox SWG-M204 Wireless Gateway with 4 GSM Channels (SWG-M204G)

The OpenVox SWG-M204G provides 4 GSM channels. They can bring you excellent HD voice service with multiple codecs, including G.711U, G.711A, GSM, G.722, G.726, G.729, and also flexible SMS service with multiple SMS API. The SWG-M204G is 100% compatible with Asterisk, 3CX, FreePBX, FreeSWITCH and VOS VoIP operating platform, and help users reduce telecommunications and communication costs.

OpenVox SWG-M204G Key Features

- Support SIP/IAX2 Protocol
- DTMF Mode: RFC2833/Inband/SIP Info
- SIP V2.0 RFC3261 Compliance
- Abundant Codecs:G.711A, G.711U, G.729, G.722, G.726, GSM
- Work as both SIP Client and Server mode
- IPv4&#65292;UDP/TCP&#65292;ARP, DHCP, NTP, DNS, HTTP/ HTTPS, SSH
- PPTP VPN
- Ping & Traceroute
- Firewall
- Friendly GUI and easy configuration
- WEB/SSH Access and Management
- Support configuration files backup and restore
- Support multiple languages
- Firmware Update by Web
- CDR
- Detailed Log
- Network and SIP capture
- SIP/IAX2/Wireless Group Settings
- Random call interval
- Call Duration Limitation
- Open API Protocol (based on Asterisk)
- Two-stage dialing
- Multiple SMS API
- SMS/USSD
- PIN Identification
- SMS Bulk Transceiver and Auto Resend
- SMS to Email
- SMS Forwarding and Quick Reply
- SMS Remotely Controlling Gateway
- Flexible Call Routings
- Schedule Reboot
- Support MMP
- Support for Custom Scripts, Dialplans
- Support OpenVox Cloud Service
- CLID Display & Hide (Need operators's support )

OpenVox SWG-M204G - Technical Specifications

General

• Module Type: GSM

## OpenVox SWG-M204 Wireless Gateway with 4 GSM Channels (SWG-M204G)

Module Number: 4  
Channel Number: 4  
Band: GSM:850/900/1800/1900MHz  
Weight (without antenna): 527g  
Power: 28W  
Dimension (without antenna): 206\*125\*27mm  
SIM Card: Hot-Swap  
LAN: 1\*10/100M  
WAN: 1\*10/100M  
Operation Temperature: 0~40°C;  
Operation Humidity Range: 10% ~ 90%  
Storage Temperature Range: -20~70°C;

**Price: £262.10**

---