

Grandstream GSC3610 Infrared Weatherproof Fixed Dome IP Camera



Product Name: Grandstream GSC3610 Infrared Weatherproof Fixed Dome IP Camera

Manufacturer: -

Model Number: GSC3610

Please Note: This product has been discontinued. For an alternative, please see other IP cameras on our new site UX.

Grandstream GSC3610 Infrared Weatherproof Fixed Dome IP Camera

The Grandstream GSC3610 is a weatherproof infrared (IR) ceiling-mounted fixed dome IP camera with a 3.6mm lens - making it an ideal device for wide-angle monitoring of nearby subjects in environments such as banks, hotels, retail stores, offices, warehouses, and building entrances. This device supports motion detection and smart infrared technology for white balance and exposure to monitor activity at night in outdoor or dark enclosed spaces. Grandstream GSC3610 Key Features

- ï¿1/2 Supports motion detection
- ī¿½ Smart infrared technology for optimal white balance and exposure
- រ៉េ¿½ Built-in PoE to power the device and provide a network connection
- าั¿½ Supports alert notifications via outbound voice or video call & amp; email screenshot
- 12.1/2 IP66-level weatherproof capability
- 12.1/2 Primary stream 1920x1080 and Secondary stream 640x480
- ī సైస్ట్ SIP/VoIP support for video and audio streaming to endpoints (external microphone required)

The GSC3610 can be managed with GSURF Pro, Grandstream's free video management software, along with other ONVIF-compliant video management systems. It pairs with Grandstream's video phones and GSC3570 HD intercom and facility control station for active end-point monitoring and facility control. By adding weatherproof capabilities, this is an ideal device for increasing security and facility management in any indoor or outdoor area. Grandstream GSC3610 - Technical Specifications General

Τέ½ Network Protocol: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, 802.1x, TLS, SRTP

- تزاري Image Sensor Resolution: 1/2.9" CMOS Sensor, 1920(H)*1080(V)
- � Video Compression: H.264/H.265/JPEG/MJPEG
- าั¿½ Supported Maximum Video Resolution and Frame Rate:- Primary Stream:1920*1080-

Secondary Stream: 640*480 i¿½ Video Output: Network

- Ti. 1/2 Audio:- Line-In: 1 x 3.5mm, 1-50mVpp;- Line-Out: 1 x 3.5mm, 560Ω, 4.0Vpp
- � Scanning System: Progressive
- � Image Configuration: Saturation/Brightness/Contrast/Sharpness, White Balance
- � Focal Length: Fixed 3.6mm
- � Infrared LED: 2x LED, up to 20M, Auto Control
- าั¿1/2 Ethernet: One RJ-45 (10/100Base-T) Port with PoE
- ï¿1/2 ONVIF: Yes, Profile S
- าั¿½ Day/Night: Colour/ Black& White (IR-CUT)
- ï¿1/2 Motion Detection: Supported
- � Langauge Supported: Multi-Language
- آذِ1/2 Privacy Mask: 4 Rectangular Zone
- ī సైస్త Weatherproof Grade: Metal , IP66-level weatherproof capability



Grandstream GSC3610 Infrared Weatherproof Fixed Dome IP Camera

Ti21/2 Power:- DC12V±10%,1A (Power Adapter NOT Included)- PoE: Support IEEE 802.3af

آذ½ Temperature / Humidity: -20 °C ~ 50 °C, RH95% Max

ï¿⅓ Weight and Dimensions: 109 x 93mm, 390g

� Compliance: FCC, CE, RCM, IC

Price: £40.00