



Product Name: Yealink T33P Entry Level IP Phone (SIP-T33P)

Manufacturer: -

Model Number: SIP-T33P

Please Note: This product has been discontinued. For an alternative, please see the Yealink T33G.

Yealink T33P Entry Level IP Phone (SIP-T33P)

The Yealink T33P is an entry-level color screen IP phone with high performance, Yealink SIP-T33P offers support for 4 lines and includes local 5-way conferencing. For its fashionable appearance as well as an extra-large 320x240-pixel colour display with backlight, it brings comfortable operation experience and clear visual experience for users. Designed with a new powerful chip, it helps greatly improved work efficiency. Additional features include the dual 10/100 Mbps network ports with integrated PoE, EHS35 support for Yealink wireless headset and adjustable multi-angle stand support. These features allow the SIP-T33P to be a high-quality but cost-effective classic IP phone that maximises productivity in both small and large office environments.

Yealink T33P Key Features

آزٰ Yealink HD Voice

� 2.4" 320 x 240-pixel colour display with back-light

ï¿1/2 Two-port 10/100M Ethernet Switch

� PoE support

� Opus codec support

ï¿1/2 Up to 4 SIP accounts

ï¿1/2 Local 5-way conferencing

ï¿1/2 Support EHS Wireless Headset

ï¿⅓ Unified Firmware

� Support YDMP/YMCS

ï¿1/2 Stand with 2 adjustable angles

ï¿1/2 Wall mountable

Stronger Performance, More Possibilities Equipped with powerful chip, the T3 series owns a stronger computing ability and more upgraded functions, which ensures a higher productivity and smoother office experience. Due to great performance, T3 series is capable to extend more services for different business demands.

Superior HD Audio, Better Communication The Yealink T3 series provides distraction-free communications with industry leading Smart Noise Filtering Technology, which delivers excellent sound quality without extraneous noises and allows fluent conversations.

Classic Design, Practical Details Designed by Yealink original team, T3 series inherits the design concept of Yealink IP phone family. The advanced design including modern appearances and ergonomic details enables easier and friendly operation experience to users.

All in One Platform, Convenient Management Proven reliability and integrations for Yealink Device Management Platform, installed the unified firmware, T3 series is simple to deploy and manage, which allows a significant reduction in the operation and maintenance cost.

Yealink T33P - Technical Specifications

Audio Features

ï¿1/2 HD voice: HD handset, HD speaker

ï¿1/2 Smart Noise Filtering

ï¿1/2 Wideband codec: Opus, G.722

� Narrowband codec: G.711(A/μ), G.723.1, G.729AB, G.726, iLBC

าั¿½ DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO



- าั¿1/2 Full-duplex hands-free speakerphone with AEC
- � VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- ï¿1/2 4 VoIP accounts
- � Call hold, mute, DND
- ï¿1/2 One-touch speed dial, hotline
- � Call forward, call waiting, call transfer
- � Group listening, SMS, emergency call
- � Redial, call return, auto answer
- � Local 5-way conferencing
- � Direct IP call without SIP proxy
- � Ring tone selection/import/delete
- � Set date time manually or automatically
- تز½ Dial plan
- ï¿1/2 XML Browser, action URL/URI
- ï¿⅓ Integrated screenshots
- � RTCP-XR, VQ-RTCPXR
- � Enhanced DSS Key

Directory

- � Local phonebook up to 1000 entries
- ï¿1/2 Black list
- ï¿1/2 XML/LDAP remote phonebook
- آز½ Smart dialing
- � Phonebook search/import/export
- � Call history: dialed/received/missed/forwarded

IP-PBX Features

- า๊¿½ Busy Lamp Field (BLF), Bridged Line Apperance (BLA)
- � Anonymous call, anonymous call rejection
- ï¿⅓ Hot-desking, voice mail
- ï¿⅓ Flexible seating
- ï¿1/2 Call park, call pickup
- � Executive and Assistant
- ï¿1/2 Centralised call recording
- � Visual voice mail
- � Call recording

Display and Indicator

- � 2.4" 320 x 240-pixel colour display with backlight
- � 16 bit depth colour
- � LED for call and message waiting indication
- าั¿½ Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- า๊¿1/2 Intuitive user interface with icons and soft keys
- � Multilingual user interface
- ï¿1/2 Caller ID with name and number
- ï¿1/₂ Screensaver
- � Power saving



Feature keys

� 4 line keys with LED

าั¿½ 5 features keys: message, headset, redial, mute, hands-free speakerphone

� 6 navigation keys

� Volume control keys

Interface

� 2 x RJ45 10/100M Ethernet ports

าั¿½ Power over Ethernet (IEEE 802.3af), class 2

� 1 x RJ9 (4P4C) handset port

� 1 x RJ9 (4P4C) headset port

Other Physical Features

� Colour: Classic Grey

� Wall mountable

ī¿1/2 External Yealink AC adapter AC 100~240V input and DC 5V/600mA output

� Power consumption (PSU): 2-3W

� Power consumption (PoE): 3.5-5W

� Dimension (W*D*H*T): 212mm*186mm*146mm*42mm

� Operating humidity: 10~95%

� Operating temperature: -10~50°C (+14~122°F)

Management

� Configuration: browser/phone/auto-provision

า๊ะู่ Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy

ï¿1/2 Auto-provision with PnP

� Zero-sp-touch, TR-069

آزا Phone lock for personal privacy protection

� Reset to factory, reboot

� Package tracing export, system log

Network and Security

ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)

ï¿1/2 Call server redundancy supported

� NAT traversal: STUN mode

� Proxy mode and peer-to-peer SIP link mode

� IP assignment: static/DHCP

� HTTP/HTTPS web server

า๊¿½ Time and date synchronisation using SNTP

� UDP/TCP/DNS-SRV (RFC 3263)

آذِر QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP

ï¿⅓ SRTP for voice

� Transport Layer Security (TLS)

ï¿⅓ HTTPS certificate manager

ï¿1/2 AES encryption for configuration file

� Digest authentication

� OpenVPN, IEEE802.1X

ï¿⅓ IPv6

� LLDP/CDP/DHCP VLAN

ICE ½٪ iCE



Package Features

آذًا½ Package content:- Yealink SIP-T33P IP phone- Handset with handset cord- Ethernet Cable (1.5m CAT5E UTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)

� Qty/CTN: 10 PCS � N.W/CTN: 9.6 kg � G.W/CTN: 10.57 kg

ī¿½ Giftbox size: 238 mm*210 mm*103 mm ī¿½ Carton Meas: 535 mm*443 mm*250 mm

Please Enquire

Options available for Yealink T33P Entry Level IP Phone (SIP-T33P):

Need Product Setup / Training / Support?

Required - 1 Hour (+£75.00), Not Required.

Power Supply Required?

UK PSU Required (+£3.70), Not Required.

Headset

YHS33 Headset (+£25.00), Not required.