

Yeastar P550 VoIP PBX



Product Name: Yeastar P550 VoIP PBX

Manufacturer: Yeastar

Model Number: P550

Yeastar P550 VoIP PBX

The Yeastar P550 VoIP PBX is an adaptive, professional, reliable PBX phone system for SMEs. It allows businesses to have uninterrupted communications in at all times in a fully fledged system.

Yeastar P550 Key Features

- 1/2 Users 50
- 1/2 Max Concurrent Calls 25
- 1/2 Max Call Centre Agents 50
- 1/2 Max FXS Ports 8
- 1/2 Max BRI Ports 8
- 1/2 Max GSM/4G Ports 4

PBX Plus Call CentreP-Series PBX System introduces an inbound call center solution to improve agent efficiency, responsiveness, and ultimately customer satisfaction for SMEs running service centers. Besides standard communications features, Call Distribution, Queue Panel, Wallboard, SLA, and Call Reports are all designed to support more proactive performance monitoring, reporting, and management.

PBX Plus UC ClientsDesigned to enhance communication experience and efficiency, Linkus UC Clients allow P-Series PBX users to easily access a comprehensive suite of calling, conference, voicemail, presence, enterprise contacts, collaboration from a single interface using mobile phones, desktops, and web browsers. Employees can stay connected with colleagues and customers where, when, and however they prefer.

Contacts DirectoryP-Series PBX System makes it easy and intuitive to organise contacts for SMEs. Users can both add external contacts to create a centralized, company-wide directory and manage their personal contact entries, benefiting from the caller ID match and speed dial. Either company or personal contacts will be synced across Linkus UC Clients, enabling easy access and dialing for in-office, mobile, and remote workers

Remote WorkingP-Series PBX System helps SMEs adapt to the new normal of working from home by enabling BYOD mobility, reducing security and network administration challenges, supporting remote control and management, and combining team collaborations. With teleworkingfriendly features available out of the box, the dispersed teams unified under the same PBX system can remain engaged and productive.

Yeastar P550 - Technical Specifications

General

- 1/2 Users 50
- 1/2 Max Concurrent Calls 25
- 1/2 Max Call Center Agents 50
- 1/2 Max FXS Ports 8
- 1/2 Max FXO/BRI Ports 8
- 1/2 Max GSM/3G/4G Ports 4
- 1/2 Transport Protocol UDP, TCP, TLS, SRTP
- 1/2 Voice Codec G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC
- 1/2 Video Codec H263, H263P, H264, MPEG4
- 1/2 DTMF In-band, RFC4733, RFC2833, SIP INFO
- 1/2 NFC Read/Write
- 1/2 Ethernet interfaces 2 x (10/100/1000 Mbps)
- 1/2 USB 1 (up to 2TB)
- 1/2 Power Supply AC 100-240V 50/60HZ 0.6A max

Yeastar P550 VoIP PBX

½ Size (L x W x H) (cm) 34 x 21 x 4.4

½ Weight 1.64 kg

½ Form Factor 1U Rack-mount

½ Environment

½ Operation Range: 0°C to 40°C, 32°F to 104°F

½ Storage Range: -20°C to 65°C, -4°F to 149°F

½ Humidity: 10-90% non-condensing

Price: £1,016.70
