

2N Access Unit 2.0 RFID 13.56MHz (9160342)

100	and and a second	-
1.3		
102		٠
	(((+)))	
11.2		

Product Name: 2N Access Unit 2.0 RFID 13.56MHz (9160342) Manufacturer: 2N Telecommunications Model Number: 9160342

2N Access Unit 2.0 RFID 13.56MHz (9160342)

The 2N Access Unit 2.0 RFID 13.56MHz is an access control unit based purely on IP technology. It combines the functions of a traditional door controller and RFID reader with 13.56MHz frequency. Thanks to wireless NFC technology, you can easily open the door using a smartphone with the 2N Mobile Key application installed. 2N Access Unit 2.0 RFID 13.56MHz Key Features

Minimum wiring requirements Same design as IP intercoms i¿½ NFC support

i¿1/2 Advanced event reporting

� Monitors entrances and exits

ï¿1/2 Remote configuration and administration

� Attendance terminal

2N Access Unit 2.0 RFID 13.56MHz Technical Specification Interfaces

- ï¿1/2 Power supply: PoE and/or 12V/1A DC
- ï¿1/2 PoE: 802.3af (Class 0–12.95W)
- � LAN: 10/100BASE-TX with Auto-MDIX, RJ-45 modular jack
- ï¿¹/₂ Recommended cabling: Cat-5e or better
- ï¿1/2 Active switch output: 8 to 12V DC / max 600mA
- ï¿1/2 Passive switch: NO/NC contacts, up to 30V 1A AC/DC
- ï¿1/2 Inputs: 2 inputs in passive / active mode (-30V to + 30V DC)

ï¿1/2 Tamper switch: Native part of the 2N Access Unit 2.0

ï¿1/2 Audio: Buzzer and microphone

RFID Card Reader

ï¿1/2 Frequency: 13.56MHz

ï¿1/2 13.56MHz (ISO14443A, ISO14443B, NFC support)

� reads UID (CSN)

ï¿1/2 reads PACs ID (HID iClass cards with SIO object)

Mechanical Properties

ï¿¹/₂ Cover: Robust zinc cast frame with surface finish (nickel and black colour)

ï¿1/2 Operating temperature: -40°C to 60°C

ï¿1/2 Storage temperature: -40°C to 70°C

ï¿¹/₂ Operating relative humidity: 10%-95% (non-condensing)

 $i_{\dot{c}}$ ¹/₂ Dimensions (1-module solution):- Wall (surface) mounting frame: 107 (W) x 130 (H) x 28 (D) mm - Flush mounting frame: 130 (W) x 153 (H) x 5 (D) mm- Flush mounting box (minimum hole): 108 (W) x 131 (H) x 45 (D) mm- Weight: max. 0.8kg

ï¿1/2 Cover rating: IP54 and IK08

Expansion Modules (not included)



2N Access Unit 2.0 RFID 13.56MHz (9160342)

ïزائ 2N Access Unit 2.0 supports modules from the 2N® IP Verso intercom: RFID card readers, keypad, fingerprint, Bluetooth, I/O module, Wiegand, etc.

Price: £351.30