

## 2N Access Unit 2.0 Secured RFID 13.56MHz (9160342-S)



Product Name: 2N Access Unit 2.0 Secured RFID 13.56MHz (9160342-S)

Manufacturer: 2N Telecommunications

Model Number: 9160342-S

### 2N Access Unit 2.0 Secured RFID 13.56MHz (9160342-S)

The 2N Access Unit 2.0 Secured RFID 13.56MHz is an access control unit based purely on IP technology. It combines the functions of a traditional door controller and RFID reader with 13.56MHz frequency. Thanks to wireless NFC technology, you can easily open the door using a smartphone with the 2N Mobile Key application installed.

### 2N Access Unit 2.0 Secured RFID 13.56MHz Key Features

#### Minimum wiring requirements

Same design as IP intercoms

• NFC support

• Advanced event reporting

• Monitors entrances and exits

• Remote configuration and administration

• Attendance terminal

### 2N Access Unit 2.0 Secured RFID 13.56MHz Technical Specification

#### Interfaces

• Power supply: PoE and/or 12V/1A DC

• PoE: 802.3af (Class 0&ndash;12.95W)

• LAN: 10/100BASE-TX with Auto-MDIX, RJ-45 modular jack

• Recommended cabling: Cat-5e or better

• Active switch output: 8 to 12V DC / max 600mA

• Passive switch: NO/NC contacts, up to 30V 1A AC/DC

• Inputs: 2 inputs &ndash; in passive / active mode (-30V to + 30V DC)

• Tamper switch: Native part of the 2N Access Unit 2.0

• Audio: Buzzer and microphone

#### RFID Card Reader

• Frequency: 13.56MHz

• 13.56MHz (ISO14443A, ISO14443B, NFC support )

• reads UID (CSN)

• reads PACs ID (HID iClass cards with SIO object)

#### Mechanical Properties

• Cover: Robust zinc cast frame with surface finish (nickel and black colour)

• Operating temperature: -40&deg;C to 60&deg;C

• Storage temperature: -40&deg;C to 70&deg;C

• Operating relative humidity: 10%-95% (non-condensing)

• Dimensions (1-module solution):- Wall (surface) mounting frame: 107 (W) x 130 (H) x 28 (D) mm - Flush mounting frame: 130 (W) x 153 (H) x 5 (D) mm- Flush mounting box (minimum hole): 108 (W) x 131 (H) x 45 (D) mm- Weight: max. 0.8kg

• Cover rating: IP54 and IK08

Expansion Modules (not included)

## 2N Access Unit 2.0 Secured RFID 13.56MHz (9160342-S)

The 2N Access Unit 2.0 supports modules from the 2N® IP Verso intercom: RFID card readers, keypad, fingerprint, Bluetooth, I/O module, Wiegand, etc.

**Price: £435.60**

---