

## 2N Access Unit M RFID 13.56 MHZ Secured (916112-S)



Product Name: 2N Access Unit M RFID 13.56 MHZ Secured (916112-S)

Manufacturer: -

Model Number: 916112-S

Please Note: This product has been discontinued. For an alternative, please see the other 2N products.

2N Access Unit M RFID 13.56 MHZ Secured (916112-S)

The 2N Access Unit M RFID 13.56 MHZ Secured can read most cards at a frequency of 13.56 MHz. It is suitable for companies which prefer traditional RFID technology. The reader supports NFC technology, so employees who don't want to wear a card can use their mobile phone to gain access. Administer a unit remotely via the secure web interface or in the 2N® Access Commander software.

2N Access Unit M RFID 13.56 MHZ Secured Key Features

- Slimline design
- Fastest mobile access
- Controller and reader in one
- Perfect for the office or outdoor
- Quick installation
- Encrypted two-way communication

2N Access Unit M RFID 13.56 MHZ Secured Technical Specifications  
Interfaces

- Power supply: PoE and/or 12 V/1 A DC
- PoE: 802.3af (Class 0&ndash;12.95 W)
- LAN: 10/100BASE-TX with Auto-MDIX, RJ-45 female (pigtail)
- Recommended cabling: Cat-5e or better
- Active switch output: 8 to 12 V DC/max 600 mA
- Passive switch: NO/NC relay, 30V 1A AC/DC
- Inputs:- 2 inputs &ndash; in passive / active mode (-30 VDC to + 30 VDC)- OFF = OPEN or Uin > 1.5 V- ON = CLOSED or Uin < 1.5 V
- Tamper switch: native part of the 2N Access Unit M
- Audio: buzzer, 1 W/8ohm
- Supported protocols: DHCP opt. 66, SMTP, TFTP, HTTP, HTTPS, Syslog

Mechanical properties

- Cover: tempered glass with rugged plastic
- Operating temperature: -40&deg;C to 60&deg;C
- Storage temperature: -40&deg;C to 70&deg;C
- Operating relative humidity: 10%-95% (non-condensing)
- Dimensions (surface mounted): 50 (W) x 133 (H) x 27 (D) mm
- Weight max 0.5kg
- Cover rating IP55 and IK07

Bluetooth

- Version: compatible with Bluetooth 5.0 LE
- Range: adjustable (short ~ 0.5m, medium ~ 2m long ~ up to 10 m)

## 2N Access Unit M RFID 13.56 MHZ Secured (916112-S)

• Security: RSA-1024 and AES-128 encryption

• RX sensitivity: up to 94.8 dBm

Mobile Application Support

• Android 6.0 and higher, iOS 12.0 and higher

RFID Card Reader

• Supported frequencies: 13.56MHz variant (optionally secured); 125kHz and 13.56MHz variant (optionally secured 13.56 MHz)

• 125kHz: EM4100, EM4102, HID Prox

• 13.56MHz: ISO14443A, ISO14443B, NFC support reads UID (CSN) reads PACs ID (HID iClass cards with SIO object)

**Please Enquire**

---