

Algo 8039 IP Video Mullion Intercom



Product Name: Algo 8039 IP Video Mullion Intercom

Manufacturer: Algo

Model Number: Algo-8039

Algo 8039 IP Video Mullion Intercom

The Algo PoE 8039 IP Video Mullion Intercom is a wide-angle IP video intercom designed for hands-free visitor communication at a secure door entrance framed in a mullion. The narrow footprint of this intercom is ideal for installation on mullion door frames, however, the 8039 can be mounted to any surface for intercom communication at gates and other building entry and access points. This IP video intercom / doorphone is outdoor-rated and is also a fully compliant 3rd party SIP endpoint. As a result, the 8039 is compatible with most hosted / cloud and premise-based VoIP telephone systems.

Key Features:

- Wideband HD voice for high intelligibility.
- Initiates or accepts intercom calls.
- 187 degree field of view from a web browser or any H.264 video enabled telephone.
- Outdoor rated – Type 3R (IPX3).
- Configuration via user friendly web interface or auto-provisioning.
- PoE (IEEE 802.3af).
- Configurable backlit tactile silicon rubber keypad, featuring auto-attendant capability.
- Ideal for door / gate entry, in addition to controlling access points to elevators and secure areas such as a day care, hospital ward, lab or data center.

UC Integration

The 8039 IP Video Mullion Intercom provides flexible communication options and the ability to answer using a standard telephone, softphone client or smartphone. Integration with a VoIP telephone system extends the reach of the intercom to all users on the UC platform having a telephone regardless of whether the device is video-enabled or not.

Fisheye Camera Lens & Wide Angle Field of View

A fisheye camera lens and de-warp algorithm allows visibility directly beneath the intercom as well as 90 degrees left and 90 degrees right. An intuitive web interface provides the capability to “see” what the intercom “sees” at any time from any browser. This security detection feature and wide angle field of view provides visibility if a visitor were to try and step away from the intercom to avoid being seen. Similarly, line of sight below the intercom can assist with incidents where a visitor is having difficulty and fallen to the ground, for example.

Configurable Keypad

In addition to access control functions, the 8039 keypad can be configured in several ways for visitors including simple one-button calling, extension dialing, or as an integrated auto-attendant feature which plays a custom recorded WAV file in response to a key press. For example, “Welcome to our school, please press one for office, two for staff room, three for day care.”

Integrated Door / Gate Access Control

For maximum user convenience, the 8039 allows momentary door unlock control activated by a keypress from the 8039 intercom or via the telephone answering device. This requires the optional 8063 IP Door Controller which can be securely located away from the public facing intercom. Alternatively, an internal relay on the 8039 is available for door control function with lower security. To sum up, the 8039 is an outdoor rated IP video intercom / doorphone. The endpoint is powered via PoE (IEEE 802.3af). A surface mount bracket is included for easy wall installation. The product is CSA/UL, FCC and CE certified.

Benefits of the PoE Algo IP Video Mullion Intercom

Algo 8039 IP Video Mullion Intercom

- Video intercom with 187 degree field of view.
- Fits a mullion door frame where standard intercoms do not mount properly.
- Configurable keypad featuring auto-attendant capability.
- Network managed and supervised SIP endpoint.
- Eliminates FXS port or ATA.
- PoE (IEEE 802.3af) for plug and play network connectivity.
- Wideband G.722 HD voice audio for clarity and intelligibility.
- Suitable for public access and outdoor environments.
- Seamless relay activation via telephone or intercom keypad for secure door or gate entry.
- Internal memory of 1GB for uploading custom WAV files (e.g., auto-attendant announcements).
- Compatible with any third-party SNMP monitoring software or the Algo 8300 IP Endpoint Supervisor (Controller).

Algo 8039 IP Video Mullion Intercom - Technical Specifications

Power:

- Power Input: PoE (IEEE 802.3af Class 0) 48V, 12.95W
- Max Power: 10W
- Idle Power: 4W

SIP:

- SIP Extensions: 1 Intercom Extension
- SIP Signalling: UDP/TCP/TLS/RTP

Audio:

- Microphone: Single Wideband
- Audio Codecs: G.711 u-law, G.711 A-law, G.722 Wideband
- Audio Memory: 1 GByte audio storage

Video:

- Video Codecs: H.264 Main or high profile
- Resolution: 720p, VGA, CIF up to 30fps
- Image Sensor: 187 Degree FOV horizontal and vertical. Fisheye image de-warped

Environmental and Mechanical:

- Environmental: -40 to +50°C (-40 to +122°F); Rated for outdoor environments Type 3R (IPX3)
- Dimensions: 10.4" x 1.95" x 1.64" (26.3 cm x 4.95 cm x 4.17 cm)
- Weight: 2.6 lbs (1.2 kg)
- Keypad Functions: Press any key to call; access control; dial number directly; directory annunciation.
- Enclosure: Metal

Compliance:

- RoHS, CE, FCC Class A, CISPR 22 Class A, CISPR 24, CSA/UL (USA & Canada), EN60950

Algo 8039 IP Video Mullion Intercom

Price: £1,427.40
