

## Fanvil i63 SIP Video Door Phone (i63)



Product Name: Fanvil i63 SIP Video Door Phone (i63)

Manufacturer: Fanvil

Model Number: i63

### Fanvil i63 SIP Video Door Phone (i63)

The Fanvil i63 is a SIP Video Door Phone that integrates powerful functionalities of access control, an intercom, and security protection. The i63 features an aluminum alloy design and 5 speed-dial buttons with a high-quality luxury appearance. Featuring IP66 and IK07 protection, it is waterproof, dustproof and has anti-collision in most outdoor environments.

Fanvil i63 Key Features:

- With high protection level of IP66 and IK07, wide temperature range from -40°C to 70°C, it can work perfectly in most outdoor environments
- Support to open the door with RFID/IC cards, indoor switch, remote DTMF, Timed open door
- Aluminum alloy design and 5 speed-dial buttons
- Built-in 2M pixels wide-angle camera: 120°(H), 60°(V) with infrared night-vision feature
- Fitted with a tamper switch that detects unauthorized opening of the device itself
- Compatible with SIP and ONVIF protocols
- Built-in 3 short-in detect ports and 2 short-out control ports, can be integrated with induction loop antenna
- Built-in maximum 128GB capacity TF card slot for image storage
- HD voice speech quality with built-in 2.5W speaker and Acoustic Echo Canceller

### Luxury and Elegant

Designed with an aluminum alloy finish, the i63 combines technology and art. The 5 speed-dial buttons with blue backlight enable users to see clearly even in low light conditions

### Strong and Durable

Featuring highly waterproof and dustproof casing with anti-collision grade material, the i63 has great performance in different outdoor environments. The anti-tamper alarm will report to the control center when the cover is unauthorized opened.

### Smart and Convenient

The Fanvil i63 allows users to achieve smart access control with RFID/IC cards, indoor switch, remote DTMF and Timed open door. It provides clear video images even in dark with an infrared night-vision camera.

### Thoughtful and Helpful

The i63 is able to be integrated with induction loop antenna, providing a better experience for users with hearing impairment.

### Linkage with Security System

With rich input and output interfaces, the i63 can be connected with 3rd party devices. It is easy to be integrated with security products in different solutions, reducing investment cost and safeguarding the security of communities.

### Remote Access Control with Mobile Phone

Residents can communicate with visitors and easily identify visitors via mobile phone APP. With one-click door opening feature, it saves lots of time and greatly improves management efficiency.

### Zero Touch Deployment

Fanvil Device Management System (FDMS) enables users to realize plug-and-play and efficient auto-provisioning online, realizing the remote management and upgrade.

### Fanvil i63 - Technical Specifications

#### i63 Video Door Phone

• 2 SIP lines

• Video intercom

## Fanvil i63 SIP Video Door Phone (i63)

- IP address announcement in English
- Programmable DSS key
- RS485 port: Support
- Wiegand port: Support
- Switch signal input and output
- Door control in and out
- Line-out for induction loop antenna: Support
- Support TF card
- PoE enabled
- Open the door operation: DTMF, RFID card, indoor switch, Time open door
- RFID cards (support 10,000)
- Door open records (support 200,000)

### Device Functions

- Auto-answering
- Programmable DSS keys
- Through button or web page volume adjustment
- Network time synchronization
- Time Plan (task management)
- Dynamic multicast function
- SIP call multicast function
- HTTP API
- Action URL / Active URI

### Call Functions

- Call out / answer / reject
- Call waiting
- Intercom, Multicast
- Speed dial
- Anonymous call (Hide caller ID)

### Audio

- Narrowband codec: G.711A/U, G.729A/B, iLBC, G.723.1, G.726-32K
- Wideband codec: G.722, Opus
- Full-duplex hands-free speakerphone with AEC
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)

### Video

- Sensor: 1/2.9" color CMOS
- Pixels: 2 Mega
- Video coding: H.264
- Motion detection
- Resolution:

- Main stream 1080P@30fps
- Sub stream VGA@30fps

- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Viewing angle:

## Fanvil i63 SIP Video Door Phone (i63)

• Diagonal: 141°;  
• Horizontal: 120°;  
• Vertical: 60°;

### Network

• Physical: 10/100 Mbps Ethernet  
• IP mode: IPv4/IPv6/IPv4&IPv6  
• IP configuration: Static IP / DHCP / PPPoE  
• VPN: L2TP / OpenVPN  
• VLAN

### Protocols

• SIP v1 (RFC2543), v2 (RFC3261) over UDP/TCP/TLS  
• RTP/RTCP/SRTP  
• STUN  
• DHCP  
• IPv6  
• PPPoE  
• L2TP  
• OpenVPN  
• SNTP  
• FTP/TFTP  
• HTTP/HTTPS  
• TR-069

**Price: £163.20**

Options available for Fanvil i63 SIP Video Door Phone (i63) :

### Mounting Options

Not required, [Fanvil EX102 Flush Mount Kit \(+£25.50\)](#).

### RFID Card

[I6 Series Free Access Control RFID Card](#).