

Yealink CP930W-Base SIP Cordless Phone System



Product Name: Yealink CP930W-Base SIP Cordless Phone System Manufacturer: -Model Number: CP930W-Base

Please Note: This product is end of life. For an alternative, see the other Yealink Voice Conference Solutions.

Yealink CP930W-Base SIP Cordless Phone System The Yealink CP930W Wireless DECT Conference Phone allows you to hold meetings wherever or whenever is convenient for you. Working with the Yealink W60B base station, which owns the DECT radio coverage up to 50m indoors, the CP930W can provide good and stable signal.CP930W Key Features:

i¿½ DECT technology i¿½ Up to 8 concurrent calls i¿½ Up to 8 DECT cordless handsets i¿½ Up to 8 VoIP accounts

CP930W Key Features:

� Built-in battery
� Up to 24-hour talk time
� Up to 15-day standby time
� Less than 4 hours charging time
� Optima HD voice, full duplex technology
� 20-foot (6-meter) and 360-degree microphone pickup range
� 5-way conference call
� Upgrade over the air

Thanks to its built-in battery and the DECT technology, the CP930W entirely frees you from thenetwork and power outlets troubles, giving you a tidy conference table with only one elegan tCP930W. Also, its built-in rechargeable battery ensures up to 24 hours of call time and 15 daysof standby time, guaranteeing a long working time without recharging and making the CP930W totally wireless in DECT environment. The Yealink CP930W DECT conference phone, marrying the Yealink Noise Proof Technology, unburdens the business conversation by reducing annoying noise and minimizing distractionsto set audio experience into a new level. Thanks to its built-in 3-microphone array, the CP930W owns a 20-foot (6-meter) and 360-degree voice pickup range as if all participants are sittingacross the table from each other. Morever, pairing the Yealink CP930W with your smartphone (via Bluetooth) or PC/tablet (via microUSB) allows you to turn the Yealink CP930W into a loudspeaker and microphone with ease thatthe collaboration may be easier than ever before.

Yealink CP930W-Base - Technical Specifications Phone Features

ï¿1/2 Up to 8 simultaneous calls

ï¿¹/₂ Up to 8 handset (CP930W works as a handset)

ï¿1/2 Up to 8 SIP accounts (only one SIP account on CP930W)

 $i_{i_{2}}i_{2}$ Up to 5 repeaters per base station (RT20/RT20U)

 $i_{2}i_{2}$ Up to 6 repeaters per base station (RT30)

ï¿1/2 Paging, intercom, dial plan

ï¿1/2 Call hold, call transfer, 5-way conference (CP930W only)



Yealink CP930W-Base SIP Cordless Phone System

- ï¿1/2 Switching between calls
- ï¿1/2 Call waiting, mute, silence, DND
- ï¿1/2 Caller ID with name and number
- ï¿1/2 Anonymous call, Anonymous call rejection
- ï¿1/2 Call forward (always/busy/no answer)
- ï¿1/2 Speed dial, voicemail, redial
- ï¿1/2 Message Waiting Indication (MWI)
- $\ddot{\iota}_{2}^{1/2}$ Music on hold (server-based)
- ï¿1/2 Local phonebook for up to 800 entries (store in the base, 100 entries in each handset)
- ï¿1/2 Remote phonebook/LDAP
- ï¿1/2 Phonebook search/import/export
- ï¿1/2 Call history (all/missed/placed/received)
- ï¿1/2 Direct IP call without SIP proxy
- ï¿1/2 Reset to factory, reboot
- ï¿1/2 Keypad lock, emergency call
- ï¿1/2 Broadsoft directory, BroadSoft call log
- ï¿1/2 Broadworks feature key synchronization
- ï¿1/2 Shared Call Appearance (SCA)

Management

- ï¿1/2 Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- ï¿¹⁄₂ Auto-provision with PnP
- ï¿1/2 Handset upgrade: OTA (Over-The-Air)/USB port
- ï¿1/2 Configuration: browser/phone/auto-provision
- $\ddot{\imath} \grave{\imath} \rlap{1}_2$ Trace package and system log export

Audio Features

- ï¿1/2 Full-duplex speakerphone
- ï¿1/2 Receiver volume control
- ï¿1/2 Ringer volume control
- ï¿1/2 Multiple advisory tones
- ï¿1/2 Acoustic warning for low battery status

See Datasheet at the top of the page under Documents and Manuals for more information

Please Enquire