

Snom D717 Entry-Level IP Phone - White Label



Product Name: Snom D717 Entry-Level IP Phone - White Label

Manufacturer: Snom Model Number: D717-WL

Please Note: This product is white label and available for you to add your own branding. We have a minimum order quanity of 10 on this unit. Please enquire or give us a call on 0330 088 0195 for more information.

Snom D717 Entry-Level IP Phone - White Label

The Snom D717 features an intuitive design with advanced technology and connectivity. Three self-labelling programmable feature keys sit next to a 2.8-inch, 320 x 240 pixel color LCD display. Opus codec support gives you the freedom to enjoy crystal-clear audio or high-quality narrowband audio, depending on your network conditions. Snom D717 Key Features

- าั¿1/2 High-resolution 2.7" graphical TFT display
- ï¿1/2 3 self-labelling function keys
- تز1/2 Wideband hands-free talking (speakerphone)
- าั¿1/2 Digital Signal Processor (DSP) enhanced audio quality
- تزرير 2-port Gigabit Ethernet switch (RJ45)
- آذِر Power over Ethernet IEEE 802.3af, Class 2
- � USB headset ready
- � D7 Expansion Module ready
- � Support for USB WiFi stick
- าั¿½ Electronic Hook Switch (EHS)(1) support for wireless headsets
- $\ddot{\imath}$ bual-angle footstand: 46° and 28°

Zero touch provisioning eliminates the need for manual labor typically involved with installation. Power over Ethernet (PoE) support and dual Ethernet ports makes the system cost-effective and easy to use. The USB port allows additional connectivity, including up to three D7 expansion modules for increased visibility and one-button options. The system features multiple configurations, including three programmable feature keys, four soft keys and 14 dedicated feature keys. You'll feel safe with powerful security features like VPN support.

Snom D717 Technical Specifications

Phone Features

ï¿1/2 6 SIP identities / accounts

- ï¿⅓ XML browser
- ï¿1/2 Call lists for dialed, received, missed calls
- ï¿1/2 Local directory with 1000 entries
- � Multiple language support
- า๊ะไ/2 DTMF in-band / out-of-band / SIP-INFO
- � Interoperable with all major IP PBX Platforms
- آزار Speed dialing
- تز½ URL dialing
- ï¿1/2 Local dial plan
- ï¿1/2 Automatic redial on busy
- ï¿1/2 Call completion (busy/unreachable)
- � Caller identification
- � Call waiting
- � Call blocking (deny list)
- � Auto answer
- ï¿⅓ Hold



Snom D717 Entry-Level IP Phone - White Label

- آزار Music on hold
- ï¿1/2 Blind and attended transfer
- � Call forwarding
- � 3-way conferencing on the phone
- � Extension monitoring, call pickup
- � Call park, call unpark
- ï¿⅓ Multicast paging
- � DND mode (do not disturb)
- ï¿1/2 Keyboard lock
- � Client matter code (CMC)
- ï¿⅓ Unified Communications ready

Audio

� Codecs:

- ï¿⅓ G.711 A-law, μ-law
- ï¿1/2 G.722 (wideband)
- ï¿1/2 G.726, G.729AB, GSM 6.10 (FR)
- � Built-in assignable ringtones
- ï¿1/2 Comfort noise generator (CNG)
- � Voice activity detection (VAD)

Protocols

- � SIP (RFC3261)
- � DHCP, NTP
- � HTTP / HTTPS / TFTP
- � LDAP (Directory)
- � Dual Stack IPv4 / IPv6

User Interface

- � Localisation (language, time, dial tone)
- � Red LED for call indication / message waiting
- ï¿1/2 4 context sensitive keys
- า๊¿½ 3 programmable line / function keys with multicolour LEDs
- آذًا Dedicated keys for: Message, DND, directory, menu, transfer, hold, page
- ī సై Audio keys with LED indication: Mute, speakerphone, headset
- ï¿⅓ Volume key
- � 5-way navigation key
- � OK and cancel keys
- ï¿1/2 Sensor-assisted user interface

Security

- ï¿1/2 802.1X Authentication and EAPOL
- � Transport layer security (TLS)
- � SRTP (RFC3711), SIPS, RTCP
- � HTTPS server/client
- � Password-protected web interface
- � VPN support
- � VLAN (IEEE 802.1Q)



Snom D717 Entry-Level IP Phone - White Label

```
� LLDP-MED, RTCP-XR
Specifications, Weights and Dimensions
� Dimensions (approx.):
� 7.28" x 3.54" x 8.66"
ï¿1/2 With desk stand: "7.28" x 8.46" x 6.81"
ï¿1/2 Weight (approx.): 1.8 lbs
� Input voltage: 5V DC (SELV)
� Power supply: PoE or 5Vdc power adapter(1), 10 Watts
آزٰ Handset: 4P4C
آذِ1⁄2 Headset: 4P4C; Support for Snom EHS Advanced
ï¿⅓ Hearing aid compatible (HAC) handset
ï¿1/2 1 x USB 2.0 host port, Type A
� Environmental conditions:
آزا Ambient temperature: 0°C to 35°C (32°F to 95°F)
آزر Storage temperature: -10°C to 45°C (14°F to 113°F)
� Humidity: 5% to 95% (non-condensing)
� Included in delivery:
تز½ Phone Unit
ï¿⅓ Foot stand
ï¿⅓ Handset with cord
ï¿1/2 Ethernet cable
� Quick Start Guide
ï¿⅓ Color: Black
� Warranty: 3 years
```

Please Enquire

APN: 80-S065-00

ï¿1/2 Part Number: 00004397 (all markets)