

## Grandstream GDS3702 HD Audio IP Intercom System



Product Name: Grandstream GDS3702 HD Audio IP Intercom System

Manufacturer: Grandstream

Model Number: GDS3702

### Grandstream GDS3702 HD Audio IP Intercom System

The Grandstream GDS3702 is an HD Audio IP Intercom System that offers remote facility access control for buildings of all sizes. The GDS3702 includes a built-in microphone and speaker to support intercom functionality, supports integration with electric locks for locking and unlocking doors, and offers alarm-in and alarm out support for integration with existing security systems.

Grandstream GDS3702 Key Features:

- 1/2 HD audio options with up to 1.5m of audio input and 3m of audio output
- 1/2 Supports SIP calls to IP phones to facilitate communication
- 1/2 Built with a metal casing to make it weatherproof and vandal resistant
- 1/2 2 Relay for Electric Lock and Alarm out, 2 Alarm In for Exit button and door sensor
- 1/2 Integrated PoE to power the device and provide a network connection
- 1/2 Built-in microphone and speaker offers voice options and intercom functionality

The GDS3702 works with Grandstream's free management software, GDS Manager. It features SIP/VoIP technology with 2-way HD audio, IP66 level weatherproof casing, and is vandal resistant. The combination of the GDS3702, Grandstream's IP Phones, Wave mobile app, and other 3rd party IP devices provide a complete end-to-end solution for access control, and intercom needs.

### Grandstream GDS3702 - Technical Specifications

#### General

- 1/2 Network 10M/100M Auto-sensing
- 1/2 PoE PoE IEEE 802.3af Class3
- 1/2 Supply Voltage 12VDC /1A (AC power adapter not included)
- 1/2 SIP/VoIP Support Yes, broad interoperability
- 1/2 Voice Codecs G.711&mu;/a, G.722, DTMF(RFC2833, SIP INFO), AEC, ANC
- 1/2 Audio Input Built-in microphones up to 1.5m Audio
- 1/2 Output HD loudspeaker 2W, up to 3m Input 2 Optocoupler Input, Vin<15V, for door sensor or other low voltage device Output 2 Relay, 125VAC/0.5A or 30VDC/2A, Normal Open or Normal Close, for electric lock, light switch or other relative high voltage device
- 1/2 Waterproof Certificate IP66 (EN60529)
- 1/2 Vandal Resistance IK10 (IEC62262)
- 1/2 Temperature and Humidity Operation: -30&deg;C to 60&deg;C; Storage: -35&deg;C to 60&deg;C Humidity: 10% to 90% Non-condensing
- 1/2 Mounting On-Wall, In-Wall (Mount Kit required, Sold separately)
- 1/2 Dimension (HxWxD) and Weight On-Wall: 173mm x 80mm x 36mm; In-Wall: 217mm x 120mm x 11.6mm; Unit Weight: 672 gram
- 1/2 Compliance CE, FCC, IC, RCM, UKCA

**Price: £88.00**